					PERM	ait issi	JED		
City of Portland, Maine - E 389 Congress Street, 04101 Te					ermit No: 01-1537	Issue Date		CBL: 386A B	032001
Location of Construction:	Owner Name:				er Address:	- No stand of the energy		Phone:	
685 Auburn St	Neptune Prop	Neptune Properties			120 Exchange St LAND		D     none.		
Business Name:				_	Contractor Address:			Phone	
n/a	no contractor/			n/a n/a				2077560953	
Lessee/Buyer's Name	Phone:		·	Permit Type:					
n/a	n/a				gle Family				Zone:
Past Use:	Proposed Use:				it Fee:	10		T	ナトニム
Foundation	Foundation Single Family permit # 01099		Intent to 34' x 26' w foundation		\$96.00 E DEPT:	Cost of Wor \$12,00 Approved	00.00 INSPE	CEO District:  2 CTION:	
	& add 28' x 24	24' new attached garage.		De		Denied	Use Gr	) occ   oup:R3	Type:5B
Proposed Project Description:  Amendment to Permit # 010993. Add 34' x 26' house new 28' x 24' attached garage.  Mr. Ving Van Se from WAY				Signature: PEDESTRIAN ACTI		IVITIES DIST	Signatu		ne proposition of V
		shipmare to make stack is what		Actio				ed w/Conditions Denied	
	Applied For:	Г		Signa				Date:	
·	2/17/2001				Zoning	Approva	ıl 		
1. This permit application does not preclude the Applicant(s) from meeting applicable State and Federal Rules.		Special Zone or Reviews  Shoreland		ws	Zoning Appeal  Variance			Historic Preservation  Not in District or Landmark	
2. Building permits do not include septic or electrical work.	de plumbing,	☐ Wetland ☐ Flood Zone 6			☐ Miscellaneous ☐ Conditional Use ☐ Interpretation			☐ Does Not Require Review ☐ Requires Review	
3. Building permits are void if w within six (6) months of the d	ate of issuance.								
False information may invalid permit and stop all work	ate a building							Approved	
		Site	Plan		Approve	ed		Approved w/	Conditions
		Maj	Minor MM  With		Denied Date:		Da	Denied	
I hereby certify that I am the owner I have been authorized by the owne jurisdiction. In addition, if a permit shall have the authority to enter all a such permit	r to make this application for work described	med propertion as	his authorized	e prop agent	and I agree to contact the contact that the contact is a contact to the contact the contact the contact that the contact is a contact the	to conform t	o all ap	plicable laws	of this

**ADDRESS** 

DATE


DATE

PHONE

**PHONE** 

SIGNATURE OF APPLICANT

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE



# BUILDING PERMIT INSPECTION PROCEDURES Please call 874-8703 or 874-8693 to schedule your inspections as agreed upon

Permits expire in 6 months, if the project is not started or ceases for 6 months.

The Owner or their designee is required to notify the inspections office for the following inspections and provide adequate notice. Notice must be called in 48-72 hours in advance in order to schedule an inspection:

1	
, , ,	from a "Stop Work Order" and "Stop
also be contacted at this time, before any si single family additions or alterations.	
Footing/Building Location Inspec	etion: Prior to pouring concrete
MA Re-Bar Schedule Inspection:	Prior to pouring concrete
Foundation Inspection:	Prior to placing ANY backfill
raming/Rough Plumbing/Electr	ical: Prior to any insulating or drywalling
Final/Certificate of Occupancy:	Prior to any occupancy of the structure or use. NOTE: There is a \$75.00 fee per inspection at this point.
Certificate of Occupancy is not required for you if your project requires a Certificate of inspection	certain projects. Your inspector can advise Occupancy. All projects DO require a final
	cur, the project cannot go on to the next E OR CIRCUMSTANCES.
CERIFICATE OF OCCUPANIC BEFORE THE SPACE MAY BE OCCU	
Signature of applicant/designee	<u></u>
May lugh	
Signature of Inspections Official	Date /
386A BOA3	01-1537

# FAX COVER SHEET

ro: Lave Carell
COMPANY: CITY OF PERLAND
FROM: Ton DANES
DATE: FAX NUMBER:
PROJECT: THE SHAN PERSONAL AUTORIA PLAS
NUMBER OF PAGES (Including Cover Page): 2
MESSAGE:
IF YOU HAVE ANY PROBLEMS RECEIVING THIS FAX, PLEASE CALL THE PERSON SENDING IT AS SOON AS POSSIBLE.
flease call the feason sending it as soon as tossible.

THANK YOU.

FROM: ARCHETYPE PHONE NO.: 207 772 6022 JAN. 10 2002 10:16AM P2

January 10, 2002

Attn: Dave Cadell

City of Portland Building Inspector

RE: The Shaw Residence

Auburn Pines Portland, Maine

Dave,

Per our telephone conversation this morning regarding your four questions on the Shaw Residence at Auburn Pines:

- 1) The headers at the garage doors will be 5 1/4" x 9 1/2" Para=Lam Beams (per L&L Structural Design calculations)
- 2) Andersen TW210410 Double-hung Windows do indeed meet egress requirements
- 3) As I mentioned in our conversation, Simpson Strap-Ties will be used in the new garage construction. The SK drawing from L&L Structural Engineering will be used in the existing house only.
- 4) Also, as I mentioned in our conversation, the plans have already been reviewed by Archetype Architects for compliance with Sub-Division requirements, and have indeed been approved.

If you have any further questions, please feel free to give a call to either the homeowner or myself.

Sincerely,

Tom Daniels

cc: John Shaw

CBL 386H-B-37 STREET ADDRESS 685 Auburn

DATE TIME CONTACT NARRATIVE INITALS  DATE TO TOO Place of Wall
Dontin TWZJ0410 mects Foress Window Standard
Dontin TWZJ0410 mects Foress Window Standard
D'inclow Standard
Window Standard
(3) Most to top Plate of wall
Connection which Continued ion
DWG SUSI ON Strapeous Strap
Ties as indicated
Colored Colored Colored
(4) Archodura (looson for Sashivisto
70 // / 21
1/10 9 Call to Sohn Show &
Tour Dantele reguesting above
material

01 1537

All Purpose Building Permit Application

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction: (35	Hubsur	1 Stree	+	
Total Square Footage of Proposed Structu	re S	quare Footage	of Lot 193 S	7. F.
Tax Assessor's Chart, Block & Lot Chart# Block# Lot#  386 A B	Owner:	phy She	, w	Telephone: 75/ 156 0957
Lessee/Buyer's Name (If Applicable)	telephone: -	me, address & 27 Olympia Flund Mi	, st 1	Additional Color (Color) (Colo
Current use:	witz Vo	reant		
If the location is currently vacant, what wo	as prior use:			<del></del>
Project description:	١٧ .	_0\- <u>0</u> 9	47 - V	Ralanta
34126 Existing Build	gue to U	iew Found	lation	add new
Contractor's name, address & telephone:			wnea)	756-0953
Who should we contact when the permit in Mailing address:	is ready: <u> </u>	1200E		
			F	Phone:
IF THE REQUIRED INFORMATION IS NOT INCLUDENIED AT THE DISCRETION OF THE BUILDING INFORMATION IN ORDER TO APROVE THIS PER I hereby certify that I am the Owner of record of the not have been authorized by the owner to make this applipation of the property of the owner to make the applipation of the owner to make the applipation of the owner to make the application of the owner to make the application of the owner to make the application of the owner to make the owner of the owner own	PLANNING DE RMIT. The property, or tication as his/her and this application is	that the owner of re ruthorized agent. I issued. I certify that	MAY REQUI ecord authoriz agree to conf the Code Of	zes the proposed work and that I form to all applicable laws of this ficial's authorized representative
to this permit.				/ )
Signature of applicant:		Do	ite: //	1/01
This is not a permit, you may no	ot commenc	e ANY work	until the p	cermit is issued

# L & L STRUCTURAL

ENGINEERING SERVICES, INC. Six Q Street South Portland, ME 04106 Phone: (207) 767-4830 Fex: (207) 799-5432

# **Field Notes**

Client

John Shaw

Project Name: Shaw Residence, 685 Auburn Street, Portland, Maine

Project No.:

21201

Date:

December 19, 2001

Time: 12:30 PM

Weather:

Overcast & Cold

Observer (s):

Joe Leasure (L&L Str. Eng. Serv.)

### Observations:

We visited the site to review the existing framing for the building that has been moved onto the site located at 685 Auburn Street, Portland, Maine. The existing building had been cut into two pieces to facilitate moving the structure. The upper half, which was on a trailer on site, included the roof structure and the second floor walls. The lower half, which was currently supported on a temporary structure on the existing foundation, included the first and second floor structure and the first floor walls. We obtained pertinent information during our site visit regarding the existing structure and numerous structural details as constructed in the building to analyze the structure.

Our review and analysis of the existing structure was performed considering the requirements of the 1999 BOCA National Building Code. Based on the information we gathered, we identified some existing conditions that are deficient compared to current code requirements and recommendations. The existing conditions and the feasibility of the proposed repairs shall be verified in the field prior to proceeding with any repairs. The deficiencies and our proposed repairs are defined on the following pages.

The existing structure is in good condition showing no signs of deterioration nor distress. There is a minor amount of deterioration of the timber rimboard and sill at the front entry in the first floor framing. The rimboard and sill shall be replaced as required at this location. We performed our analysis using the following code stipulated loading:

- Roof (Live) Load = 42 PSF
- Floor Live Load = 30 PSF (at sleeping rooms above the first floor)
- Floor Live Load = 40 PSF (otherwise)

685 Auburn Street 12/19/01 Page 2

Utilizing the prescribed loading, we identified some deficiencies in the existing structure and proposed repairs as follows:

### FIRST FLOOR FRAMING:

- 1. The existing 2x8 @16"o.c. first floor joists are sufficient to span a maximum of 12'-4". There are two areas of the floor that exceed that span. The joists beneath the living room and the kitchen clear span 13'-4" and 12'-10" respectively. The joists that exceed the 12'-4" span shall be reinforced by installing additional 2x8 joists at every other joists (i.e. 32" on center) "sistered" to the existing joists and fastened with two rows of 16d nails at 12" on center top and bottom. Also additional Simpson U28-2 joists hangers are required on both ends of the header at the chimney.
- 2. The existing 6x10 beams are sufficient to support the floor loads as long as the new columns are installed where the existing column cap plates are located. The new columns shall be 3 1/2" diameter concrete filled lally columns supported on 2'-0" square by 10" thick concrete footings with 3-#4 reinforcing bars each way 3" clear from the bottom of the footing.
- 3. Additional columns are required beneath the existing 6x10 beam on both sides of the where the beam has been cut to accommodate the temporary steel supports that were used during moving. This will require two columns at two locations for a total of four additional columns. The column and footing construction shall be the same as defined in item #2 above.
- 4. Additional columns are required beneath the existing 6x10 beam at the ends of the beams that were cut to avoid interference with the new foundation wall. This will require three additional columns at three different locations. The new columns shall be installed 12" from the inside face of the foundation wall and at the center of the existing 6x10 beam. The column and footing construction shall be the same as defined in item #2 above.
- 5. A 2x6 pressure treated sill plate shall be installed beneath the existing sill plate. The new sill plate shall be anchored to the foundation wall with 5/8" diameter anchors spaced at 4'-0" on center. The sill plates shall be fastened together with 16d nails at 4" on center.

# **SECOND FLOOR FRAMING:**

1. The second floor joists beneath the sleeping rooms are adequate to support the code stipulated loading. However, the floor joists beneath the non-sleeping rooms that exceed the 12'-4" span shall be reinforced by installing additional 2x8 joists at every other joists (i.e. 32" on center) "sistered" to the existing joists and fastened with two rows of 16d nails at 12" on center top and bottom.

DEY, o

# **ROOF FRAMING:**

- 1. The existing 2x8 @21" o.c. roof rafters are capable of supporting a snow (live) loading of approximately 33 PSF which is inadequate to support current code stipulated roof loading of 40 PSF. The rafters shall be reinforced by installing additional 2x8 rafters at every third rafter (i.e. 63" on center) "sistered" to the existing rafters and fastened with two rows of 16d nails at 12" on center top and bottom. The new rafters shall be installed tight to the 1x ridge board and shall bear on top of the existing wall plate.
- There is an inadequate connection of the rafter with the ceiling joists to prevent the roof from "thrusting" the exterior walls outward. We propose the connection illustrated on SKS-1 attached.
- 3. The second floor walls have been cut approximately 1'-0" above the second floor to facilitate moving the building. All of the studs need to be reinforced with and additional 2x4 stud full height. Furthermore, all jack and king studs require additional studs as well. All of the new studs shall be installed tight between the top and bottom plates of the existing wall including all king studs as well. We understand that it is your intent to replace the existing windows, which will give you an opportunity to replace the jack studs with one continuous member tight beneath the bottom of the header in the existing wall as required.

JOSEPH

LEASURE


If you have any questions, please do not hesitate to call.

Sincerely.

L&L Structural Engineering Services, Inc.

Joseph H. Leasure, P.E.

Principal



ROOF SECTION - CONNECTION (TYP AT BOTH SIDES

DEC 2 8 2001

11

designed by:	JHL	SHAM SESIDENCE	I I L & L STRUCTURAL
drawn by:	JHĻ	685 AUBURN STREET	ENGINEERING SERVICES, INC.
checked by:	MFL.	PORTLAND, ME	SIX Q STREET SOUTH PORTLAND, MAINE 04106
scale:	NOTED		PHONE: (207) 767-4830 FAX: (207) 769-8432 EMAIJ LLENGGACULODM
date: 12	119/01	ROOF SECTION.	III III EMAIL TENISHAGILGEN SKS-I

# FAX COVER SHEET

TO: LAVE CAPEL
COMPANY: CIT OF PRETIANO
FROM: John Davies / John Stand
DATE: FAX NUMBER:
PROJECT: THE SHALL ESSADENCE / AUTHURN STREET
NUMBER OF PAGES (Including Cover Page):
MESSAGE: DWG.
AMERICO IS THE LETTER FROM 1.41 STRUCTURAL
ELENDERENE PENELING BUKING CONDUINGUS IN THE
SHOW PESIDENCE. MED INCUIPED IS AN UPDATED
ANT PLAN SHOWING THE MOORD MUDROOM, PLANK
POR THE NEWLY LAND OUT GARRES / HUDROOM WILL
Pouch APPER THE Howards
P YOU HAVE ANY QUARRIONS,
MON CAN CONTROT ME @ 772-6000
Durne Morrise Workers Hours
tombanes.
IF YOU HAVE ANY PROBLEMS RECEIVING THIS FAX, PLEASE CALL THE PERSON SENDING IT AS SOON AS POSSIBLE. THANK YOU.

DEC 2 8 2001

# L & L STRUCTURAL

ENGINEERING SERVICES, INC. Six Q Street South Portland, ME 04106 Phone: (207) 767-4830 Fex: (207) 799-5432

### Field Notes

Client:

John Shaw

Project Name: Shaw Residence, 685 Auburn Street, Portland, Maine

Project No.: 212

21201

Date:

December 19, 2001 Time: 12:30 PM

Weather: Overcast & Cold

Observer (s): Joe Lossure (L&L Str. Eng. Serv.)

### Observations:

We visited the site to review the existing framing for the building that has been moved onto the site located at 685 Auburn Street, Portland, Maine. The existing building had been cut into two pieces to facilitate moving the structure. The upper half, which was on a trailer on site, included the roof structure and the second floor walls. The lower half, which was currently supported on a temporary structure on the existing foundation, included the first and second floor structure and the first floor walls. We obtained pertinent information during our site visit regarding the existing structure and numerous structural details as constructed in the building to analyze the structure.

Our review and analysis of the existing structure was performed considering the requirements of the 1999 BOCA National Building Code. Based on the information we gathered, we identified some existing conditions that are deficient compared to current code requirements and recommendations. The existing conditions and the feasibility of the proposed repairs shall be verified in the field prior to proceeding with any repairs. The deficiencies and our proposed repairs are defined on the following pages.

The existing structure is in good condition showing no signs of deterioration nor distress. There is a minor amount of deterioration of the timber rimboard and sill at the front entry in the first floor framing. The rimboard and sill shall be replaced as required at this location. We performed our analysis using the following code stipulated loading:

- Roof (Live) Load = 42 PSF
- Floor Live Load = 30 PSF (at sleeping rooms above the first floor)
- Floor Live Load = 40 PSF (otherwise)

685 Auburn Street 12/19/01 Page 2

Utilizing the prescribed loading, we identified some deficiencies in the existing structure and proposed repairs as follows:

### FIRST FLOOR FRAMING:

- 1. The existing 2x8 @16"o.c. first floor joists are sufficient to span a maximum of 12'-4". There are two areas of the floor that exceed that span. The joists beneath the living room and the kitchen clear span 13'-4" and 12'-10" respectively. The joists that exceed the 12'-4" span shall be reinforced by installing additional 2x8 joists at every other joists (i.e. 32" on conter) "sistered" to the existing joists and fastened with two rows of 16d nails at 12" on center top and bottom. Also additional Simpson U28-2 joists hangers are required on both ends of the header at the chimney.
- 2. The existing 6x10 beams are sufficient to support the floor loads as long as the new columns are installed where the existing column cap plates are located. The new columns shall be 3 1/2" diameter concrete filled lully columns supported on 2'-0" square by 10" thick concrete footings with 3-#4 reinforcing bars each way 3" clear from the bottom of the footing.
- 3. Additional columns are required beneath the existing 6x10 beam on both sides of the where the beam has been cut to accommodate the temporary steel supports that were used during moving. This will require two columns at two locations for a total of four additional columns. The column and footing construction shall be the same as defined in item #2 above.
- 4. Additional columns are required beneath the existing 6x10 beam at the ends of the beams that were cut to avoid interference with the new foundation wall. This will require three additional columns at three different locations. The new columns shall be installed 12" from the inside face of the foundation wall and at the center of the existing 6x10 beam. The column and footing construction shall be the same as defined in item #2 above.
- 5. A 2x6 pressure treated sill plate shall be installed beneath the existing sill plate. The new sill plate shall be suchored to the foundation wall with 5/8" diameter anchors spaced at 4'-0" on center. The sill plates shall be fastened together with 16d nails at 4" on center.

# SECOND FLOOR FRAMING:

1. The second floor joists beneath the sleeping rooms are adequate to support the code stipulated loading. However, the floor joists beneath the non-sleeping rooms that exceed the 12'-4" span shall be reinforced by installing additional 2x8 joists at every other joists (i.e. 32" on center) "sistered" to the existing joists and fastened with two rows of 16d nails at 12" on center top and bottom.

FROM: ARCHETYPE

685 Aubum Street 12/19/01 Page 3

### **ROOF FRAMING:**

- 1. The existing 2x8 @21" o.c. roof rafters are capable of supporting a snow (live) loading of approximately 33 PSF which is inadequate to support current code stipulated roof loading of 40 PSF. The rafters shall be reinforced by installing additional 2x8 rafters at every third rafter (i.e. 63" on center) "sistered" to the existing rafters and fastened with two rows of 16d nails at 12" on center top and bottom. The new rafters shall be installed tight to the 1x ridge board and shall bear on top of the existing wall plate.
- There is an inadequate connection of the rafter with the ceiling joists to prevent the roof from "thrusting" the exterior walls outward. We propose the connection illustrated on SKS-1 attached.
- 3. The second floor walls have been cut approximately 1'-0" above the second floor to facilitate moving the building. All of the stude need to be reinforced with and additional 2x4 stud full height. Furthermore, all jack and king stude require additional stude as well. All of the new stude shall be installed tight between the top and bottom plates of the existing wall including all king stude as well. We understand that it is your intent to replace the existing windows, which will give you an opportunity to replace the jack stude with one continuous member tight beneath the bottom of the header in the existing wall as required.

If you have any questions, please do not hesitate to call.


Sincerely

L&L Strucheral Engineering Services, Inc.

Joseph H. Lessure, P.E.

Principal

JOSEPH HEASURE 10242




dealgned by: Jf	IL SHAW BESIDENCE	I I L & L STRUCTURAL
drawn by: Ji	IL 685 AUGURN STREET	ENGINEERING SERVICES, INC.
checked by: M	FL PORTLAND, ME	SOUTH PORTLAND, MARKE 04108
acole: NO.	ED	ANONE (201) 701-4844 COLON
date: 12/19/	OI ROOF SECTION.	SKS-

DEN 2 8 2001

Dec 21 01 04:26p City of Portland

(207) 874-8716

р.2



					PERMIT ISS	UED		
City of Portland, 389 Congress Street	<b>Maine - Building or Use</b> , 04101 Tel: (207) 874-870	<b>Permi</b> 3, Fax:	t <b>Application</b> (207) 874-871 <i>6</i>	Per	rmit No: Issue Date 01-1537 1 70		CBL: 386A B	032001
Location of Construction:	Owner Name:			Owne	r Address:		Phone:	
685 Auburn St	Neptune Prop			120	Exchange St	LAND		
Business Name:	Contractor Nam			Contr	actor Address:		Phone	
n/a	no contractor/	self		n/a n			20775609	953
Lessee/Buyer's Name	Phone:			Permi	t Type:		<del></del>	Zone:
n/a	n/a		] [	Sing	gle Family			R-7
Past Use: Foundation	Proposed Use: Single Family permit # 0109	Single Family / Amendatent to			\$96.00 Cost of Wor \$12,0	["	EO District: 2	
	existing build & add 28' x 24		ew foundation tached garage.		Denied Approved	Use Grou	-	Type:575
December 1 Decimal Dec						13	acc	كوانتر
l new 28' x 24' attached	# 010993. Add 34' x 26' hous		F	Signat	<del></del>	Signature:	7	and the second of the second o
Nc Mc	v foundation put in -	hut pode	stek but	Action	n: Approved Ap	proved w/Co		Denied
	_ IN MARE	Ţ		Signat	ture:	D	ate:	
Permit Taken By:	Date Applied For:	ļ			Zoning Approva	al	-	
gg	12/17/2001	<del> </del>						
	cation does not preclude the neeting applicable State and		cial Zone or Review oreland	S	Zoning Appeal  Variance		Historic Pres	
2. Building permits septic or electrica	do not include plumbing, l work.	☐ We	etland		Miscellaneous		Does Not Rec	quire Review
3. Building permits	are void if work is not started on the of the date of issuance.	☐ Flo	ood Zone	ļ	Conditional Use		Requires Rev	iew
False information permit and stop al	may invalidate a building ll work	☐ Sui	bdivision		Interpretation		Approved	
		☐ Sit	e Plan		Approved		Approved w/	Conditions
		Maj [	Minor MM M		Denied		Denied	
		Date:	1/1/1	柳	Date:	Date		
I have been authorized jurisdiction. In addition shall have the authority such permit.	m the owner of record of the na by the owner to make this appli n, if a permit for work described to enter all areas covered by su	med pro ication a d in the	s his authorized application is issuant at any reasona	prop agent ued, I	and I agree to conform I certify that the code off our to enforce the provi	to all appl	icable laws of	of this
SIGNATURE OF APPLICA	ANT		ADDRESS		DATE		PHO	NE
RESPONSIBLE PERSON I	N CHARGE OF WORK, TITLE				DATE		PHO	NE

01 1537

# **All Purpose Building Permit Application**

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.


Location/Address of Construction: 685	- Auburn Stre	et		
Total Square Footage of Proposed Structu	re Square Footo	age of Lot 9,413 5	7 F.	
Tax Assessor's Chart, Block & Lot Chart# Block# Lot# 3864 \$\mathbb{T}\$ 032	Owner: John S	han	Telephone: 75/ 156 0957	
Lessee/Buyer's Name (If Applicable)	Applicant name, address telephone: 27 Olyu Podlund	piu St W	ork: \$ 12000— e: \$ 96—	
Current use:	my Vacant			
If the location is currently vacant, what wo	as prior use:		_	
Approximately how long has it been vaca Proposed use: Signal Form.	ly	2007 - D	- ( .1	
Acjoct description. Amend larming to New Foundation add new 24 x zel attacked awage				
Contractor's name, address & telephone: Who should we contact when the permit	`	(owner)	756-0953	
Mailing address:				
		Pho	one:	
IF THE REQUIRED INFORMATION IS NOT INCLUDED IN THE SUBMISSIONS THE PERMIT WILL BE AUTOMATICALLY DENIED AT THE DISCRETION OF THE BUILDING/PLANNING DEPARTMENT, WE MAY REQUIRE ADDITIONAL INFORMATION IN ORDER TO APROVE THIS PERMIT.  If hereby certify that I am the Owner of record of the named property, or that the owner of record authorizes the proposed work and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas govered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.				
Signature of applicant.		Date: /	11/01	
This is not a permit, you may not commence ANY work until the permit is issued				

# BUILDING PERMIT INSPECTION PROCEDURES Please call 874-8703 or 874-8693 to schedule your inspections as agreed upon

Permits expire in 6 months, if the project is not started or ceases for 6 months.

The Owner or their designee is required to notify the inspections office for the following inspections and provide adequate notice. Notice must be called in 48-72 hours in advance in order to schedule an inspection:

in order to schedule an inspection:	
By initializing at each inspection time, you inspection procedure and additional fees Work Order Release" will be incurred if below.  Pre-construction Meeting: Must receipt of this permit. Jay Reynolds, Devel also be contacted at this time, before any sisingle family additions or alterations.	from a "Stop Work Order" and "Stop the procedure is not followed as stated be scheduled with your inspection team upon topment Review Coordinator at 874-8632 must
Footing/Building Location Inspec	ction: Prior to pouring concrete
NG Re-Bar Schedule Inspection:	Prior to pouring concrete
Foundation Inspection:	Prior to placing ANY backfill
Framing/Rough Plumbing/Electr	ical: Prior to any insulating or drywalling
Final/Certificate of Occupancy:	Prior to any occupancy of the structure or use. NOTE: There is a \$75.00 fee per inspection at this point.
Certificate of Occupancy is not required for you if your project requires a Certificate of inspection	Occupancy. All projects DO require a final
If any of the inspections do not or phase, REGARDLESS OF THE NOTICE	ecur, the project cannot go on to the next E OR CIRCUMSTANCES.
CERIFICATE OF OCCUPANIC BEFORE THE SPACE MAY BE OCCU	ES MUST BE ISSUED AN PAID FOR, PIED  1/4/02 Date
Signature of Inspections Official	Date
386A BOA3	01-1537



# FAX COVER SHEET

	ACEL
COMPANY:CT	my or Parisano
ROM: tan [	DANES
ATE:	FAX NUMBER:
roject: THE	SHAD PROPOSE / AUBIEL PLUS
IUMBER OF PAGES	(Including Cover Page): 2
******************	*************************************
	U HAVE ANY PROBLEMS RECEIVING THIS FAX,

PLEASE CALL THE PERSON SENDING IT AS SOON AS POSSIBLE. THANK YOU.

FROM: ARCHETYPE PHONE NO.: 207 772 6022 JAN. 10 2002 10:16AM P2

January 10, 2002

Attn: Dave Cadell

City of Portland Building Inspector

RE: The Shaw Residence

Auburn Pines Portland, Maine

Dave,

Per our telephone conversation this morning regarding your four questions on the Shaw Residence at Auburn Pines:

- 1) The headers at the garage doors will be 5 1/4" x 9 1/2" Para=Lam Beams (per L&L Structural Design calculations)
- 2) Andersen TW210410 Double-hung Windows do indeed meet egress requirements
- 3) As I mentioned in our conversation, Simpson Strap-Ties will be used in the new garage construction. The SK drawing from L&L Structural Engineering will be used in the existing house only.
- 4) Also, as I mentioned in our conversation, the plans have already been reviewed by Archetype Architects for compliance with Sub-Division requirements, and have indeed been approved.

If you have any further questions, please feel free to give a call to either the homeowner or myself.

Sincerely,

Tom Daniels

cc: John Shaw

CBL 386A-B-37 STREET ADDRESS 685 Auburn

	mn er	00\FF.		ant to				· · · · · · · · · · · · · · · · · · ·
DATE	TIME	CONTACT	NARR		$\sim$		, ,	INITALS
	(./)	Ma/0	ne	1200	V Op.	ening	He	celer
		ROOM	1<					
		1/4/	7	711-	1/2/10		/	
	(2)	CONF.	im	1WC	10410	mech	3	gress
		Wino	lou)	Sta	adage		(	Ψ
	(2)	$\bigcirc$ $\leftarrow$	1 1	4	D1 7	$-\nu$	W	I. \ (
		17001	+ 70	1000	(r) 1	$\sim$	)	1
		Conn	CT'a	2W; (	which	Conti	botte	
		DW(	1, 9	KS	0	<u> 3 Em</u>	X2501	2 5400
	•	T'02	as	ind	12000		4	
		916	1	$\mathcal{D}_{-}$		2	•	
		3//		FOT	XIE	Ting-	$\overline{\mathcal{O}}$	()
		3400	$\triangleright \lambda_i$	esp =	50-	New)	(Co)	VSFLIRE PIPO
	(4)	Arch	dur	ul b	ledde	D Fo	) 	coldivisco
<del>-,/</del>	d	70 /	1//	S.	- /	. 01	/	1
4/4	0 /		X ( (	0	Soll	L gri	ceu	9
3.3	Vaa	gr Do	W CC	66 v	Cq uc	Stille	0	BOVE
	10	stal			r			
	102 10							
						<del></del>		
.							-	
		•						
						<del>-</del> -		
			······································					

# L & L STRUCTURAL

ENGINEERING SERVICES, INC. Six Q Street South Portland, ME 04106 Phone: (207) 767-4830 Fax: (207) 799-5432

### Field Notes

Client:

John Shaw

Project Name: Shaw Residence, 685 Auburn Street, Portland, Maine

Project No.:

Date:

December 19, 2001

Time: 12:30 PM

Weather:

Overcast & Cold

Observer (s): Joe Leasure (L&L Str. Eng. Serv.)

### Observations:

We visited the site to review the existing framing for the building that has been moved onto the site located at 685 Auburn Street, Portland, Maine. The existing building had been cut into two pieces to facilitate moving the structure. The upper half, which was on a trailer on site, included the roof structure and the second floor walls. The lower half, which was currently supported on a temporary structure on the existing foundation, included the first and second floor structure and the first floor walls. We obtained pertinent information during our site visit regarding the existing structure and numerous structural details as constructed in the building to analyze the structure.

Our review and analysis of the existing structure was performed considering the requirements of the 1999 BOCA National Building Code. Based on the information we gathered, we identified some existing conditions that are deficient compared to current code requirements and recommendations. The existing conditions and the feasibility of the proposed repairs shall be verified in the field prior to proceeding with any repairs. The deficiencies and our proposed repairs are defined on the following pages.

The existing structure is in good condition showing no signs of deterioration nor distress. There is a minor amount of deterioration of the timber rimboard and sill at the front entry in the first floor framing. The rimboard and sill shall be replaced as required at this location. We performed our analysis using the following code stipulated loading:

- Roof (Live) Load = 42 PSF
- Floor Live Load = 30 PSF (at sleeping rooms above the first floor)
- Floor Live Load = 40 PSF (otherwise)

685 Auburn Street 12/19/01 Page 2

Utilizing the prescribed loading, we identified some deficiencies in the existing structure and proposed repairs as follows:

### **FIRST FLOOR FRAMING:**

- 1. The existing 2x8 @16"o.c. first floor joists are sufficient to span a maximum of 12'-4". There are two areas of the floor that exceed that span. The joists beneath the living room and the kitchen clear span 13'-4" and 12'-10" respectively. The joists that exceed the 12'-4" span shall be reinforced by installing additional 2x8 joists at every other joists (i.e. 32" on center) "sistered" to the existing joists and fastened with two rows of 16d nails at 12" on center top and bottom. Also additional Simpson U28-2 joists hangers are required on both ends of the header at the chimney.
- 2. The existing 6x10 beams are sufficient to support the floor loads as long as the new columns are installed where the existing column cap plates are located. The new columns shall be 3 1/2" diameter concrete filled lally columns supported on 2'-0" square by 10" thick concrete footings with 3-#4 reinforcing bars each way 3" clear from the bottom of the footing.
- 3. Additional columns are required beneath the existing 6x10 beam on both sides of the where the beam has been cut to accommodate the temporary steel supports that were used during moving. This will require two columns at two locations for a total of four additional columns. The column and footing construction shall be the same as defined in item #2 above.
- 4. Additional columns are required beneath the existing 6x10 beam at the ends of the beams that were cut to avoid interference with the new foundation wall. This will require three additional columns at three different locations. The new columns shall be installed 12" from the inside face of the foundation wall and at the center of the existing 6x10 beam. The column and footing construction shall be the same as defined in item #2 above.
- 5. A 2x6 pressure treated sill plate shall be installed beneath the existing sill plate. The new sill plate shall be anchored to the foundation wall with 5/8" diameter anchors spaced at 4'-0" on center. The sill plates shall be fastened together with 16d nails at 4" on center.

### SECOND FLOOR FRAMING:

 The second floor joists beneath the sleeping rooms are adequate to support the code stipulated loading. However, the floor joists beneath the non-sleeping rooms that exceed the 12'-4" span shall be reinforced by installing additional 2x8 joists at every other joists (i.e. 32" on center) "sistered" to the existing joists and fastened with two rows of 16d nails at 12" on center top and bottom.

Mills of

685 Auburn Street 12/19/01 Page 3

## **ROOF FRAMING:**

- 1. The existing 2x8 @21" o.c. roof rafters are capable of supporting a snow (live) loading of approximately 33 PSF which is inadequate to support current code stipulated roof loading of 40 PSF. The rafters shall be reinforced by installing additional 2x8 rafters at every third rafter (i.e. 63" on center) "sistered" to the existing rafters and fastened with two rows of 16d nails at 12" on center top and bottom. The new rafters shall be installed tight to the 1x ridge board and shall bear on top of the existing wall plate.
- There is an inadequate connection of the rafter with the ceiling joists to prevent the roof from "thrusting" the exterior walls outward. We propose the connection illustrated on SKS-1 attached.
- 3. The second floor walls have been cut approximately 1'-0" above the second floor to facilitate moving the building. All of the studs need to be reinforced with and additional 2x4 stud full height. Furthermore, all jack and king studs require additional studs as well. All of the new studs shall be installed tight between the top and bottom plates of the existing wall including all king studs as well. We understand that it is your intent to replace the existing windows, which will give you an opportunity to replace the jack studs with one continuous member tight beneath the bottom of the header in the existing wall as required.

If you have any questions, please do not hesitate to call.


Sincerely.

L&L Structural Engineering Services, Inc.

Joseph H. Leasure, P.E.

Principal

JOSEPH H LEASURE 6242



ROOF SECTION - CONNECTION (TYP AT BOTH SIDER)

DEC 2 8 2001

11

designed by:	JHL	SHAM SESIDENCE	IIL & L STRUCTURAL
drawn by:	JHĻ	685 AUBURN STREET	ENGINEERING SERVICES, INC.
checked by:	MFL	PORTLAND, ME	SUTH PORTLAND, MAINE 04106
scole:	NOTED		PHONE: (207) 787-4830 FAX: (207) 788-8432 EMAIL: ULEHGRACI, COM
date: 12	19/91	ROOF SECTION.	SKS-1

# FAX COVER SHEET


TO: LAVE CAPEL
COMPANY: CITY OF POPULATIO
FROM: JOH Danies / John Stand
DATE: FAX NUMBER:
PROJECT: THE ZHAN ESTOPHICE / AUTHURN STREET
NUMBER OF PAGES (Including Cover Page):
MESSAGE: DWG.
AMERICA IN THE LETTER FROM LAL BRUIGHEAL
ELGINETENS PENELING EXIGING CONDITIONS IN THE
SHOW PESIDENCE. MAD INCUIDED IS AN UPDARD
AUT FLOW SHOWING THE MOORD MUDROOM. PLANT
POR THE NEWLY LAND OUT COSENES / HUDROOM WILL
Pouch Apren de House
P YOU HAVE ANY QUEENOUS,
400 CAN CONTROT ME @ 772-6000
Durne Morrae Workers Homes
tom Parmy
IF YOU HAVE ANY PROBLEMS RECEIVING THIS FAX,

PLEASE CALL THE PERSON SENDING IT AS SOON AS POSSIBLE. THANK YOU.

Dec 21 01 04:26p City of Portland

(207)874-8716

p.2



Inspection Services Michael J. Nugent Manager



# CITY OF PORTLAND

December 17, 2001

John Shaw 27 Olympia Street Portland, Maine 04103

RE: 685 Auburn Street

CBL: 386A-B-032

**Hand Delivery** 

Dear John Shaw:

An evaluation of the property at 685 Auburn Street revealed that the property fails to comply with Section 107.1 of the 1999 BOCA Building Code of the City of Portland.

An Existing Structure was moved to this location without the required Building Permit approvals

This is a notice of violation pursuant to Section 116.2 of the Code. All referenced violations shall be corrected within 21 days of the date of this notice. Please call the number provided to schedule a re-inspection of the premises by January 9, 2002, at which time compliance will be required.

The Structure shall be removed from the property

or

A Building Permit may be approved for the installation of this Structure

Failure to comply will result in this office referring the matter to the City of Portland Corporation Counsel for legal action and possible civil penalties, as provided for in Section 116.4 of the Code.

This constitutes an appealable decision pursuant to Section 121.0 of the Code. Please feel free to contact David Caddell@874-8707 if you wish to discuss the matter or have any questions.

Sincerely

David Caddell

Code Enforcement Officer




FRONT ELEVATION


SCALE: 3/16" . I'-O"

# A. E. BROWN CO. INC.

14 ANCHORAGE PLACE SOUTH PORTLAND ME. 04:06

SCALE AS NOTED CRAMN BY DATE RE //SED DRAWING NUMBER






SCALE: 1/8" . 1'-0"

# A. E. BROWN CO. INC.


14 ANCHORAGE PLACE SOUTH PORTLAND ME. 04106


SC ALE 1/8" = 1' APPROVED DRAWN BY DATE REVISED

DRAWING NUMBER





# A. E. BROWN CO. INC. 14 ANCHORAGE PLACE SOUTH PORTLAND ME. 04106 SCALE AS NOTED APPROVED DRAWN BY REVISED TRAWING NUMBER 2230 R











TYPICAL FRAME WALL SECTION -

DETAIL WOS SCALE: N.T.S.

# A. E. BROWN CO. INC.

14 ANCHORAGE PLACE SOUTH PORTLAND ME, 04106

SC ALE 1/8" = 1'


DATE

APPROVED

DRAWN BY

REVISED


DRAWING NUMBER




# A. E. BROWN CO. INC.

14 ANCHORAGE PLACE SOUTH PORTLAND ME. 04106

SC ALE 1/8" = 1' APPROVED DRAWN BY DATE REVISED DRAWING NUMBER






# A. E. BROWN CO. INC.

14 ANCHORAGE PLACE SOUTH PORTLAND ME. 04106

SC ALE AS NOTED APPROVED DRAWN BY

DATE REVISED

DRAWING NUMBER



# A. E. BROWN CO. INC. 14 ANCHORAGE PLACE SOUTH PORTLAND ME. 04106

SC ALE AS NOTED APPROVED DRAWN BY

DATE REVISED

DRAWING NUMBER

