

DWG

S

 $\exists$ 

 $\approx$ 

 $\mathcal{O}$ 

NOTE

STANDARD

SEE

-C HOMES

ACH PROPERTY RD RD 0410

BUILDER: SILVER BEACH DBA SILVER BEA( 83 WELLWOOD I PORTLAND ME

E GROUP:
SINGLE
AMILY
NST. TYPE:

USE SONS

//05/ IE:

S | NC 12594 -6698

Homes

Modular

Vestchester Modular Reagans Mill Road, Wingdale 1 (845)832—9400 Fax (

WE 30 F

## FOUNDATION NOTES:

- 1) THE FOUNDATION PLAN IS PROVIDED FOR FOUNDATION DESIGN PARAMETERS ONLY. COMPLETE FOUNDATION ENGINEERING BASED ON SPECIFIC SITE CONDITIONS, APPLICABLE LOCAL AND STATE CODES, TO BE REVIEWED AND APPROVED BY A REGISTERED ARCHITECT OR ENGINEER IN THE STATE OF HOUSE DESIGNATION.
- 2) THE BUILDER/PURCHASER SHALL BE RESPONSIBLE FOR DESIGN, CONSTRUCTION AND CODE COMPLIANCE OF ALL FOUNDATION ELEMENTS INCLUDING (BUT NOT LIMITED TO) STRUCTURAL, PLUMBING, ELECTRICAL, HEATING, ENERGY CONSERVATION AND FIRE SEPARATION.
- 3) MINIMUM COLUMN FOOTING SIZE SHALL BE 2'-6" x 2'-6" x 10" DEEP.
- 4) CONCRETE STRENGTH TO BE A MINIMUM 3000 PSI.
- 5) LALLY COLUMN SHALL BE MINIMUM 3 1/2" STEEL PIPE.
- 6) FOUNDATION SILL SHALL BE PRESERVATIVE TREATED LUMBER (SUPPLIED AND INSTALLED BY B/P PRIOR TO HOUSE DELIVERY AND SET). THERE SHALL BE NO PROTRUSION ABOVE TOP OF SILL PLATE.
- 7) THE BUILDER/PURCHASER SHALL BE RESPONSIBLE FOR ENCLOSING THE BASEMENT STAIRS AND INSULATING THE BASEMENT STAIR WALLS IN ACCORDANCE WITH ALL APPLICABLE ENERGY CODE REQUIREMENTS

THE MAXIMUM RISER HEIGHT OF 8 1/4" AND A MINIMUM TREAD DEPTH OF 9" AND A 1" NOSING WILL BE PROVIDED ON A TREADS WITH TREAD WIDTH LESS THAN 10". THIS EXCEPTION SHALL APPLY WHEN THE STAIRS ARE A COMPONENT OF A FACTORY DESIGN WHICH SPECIFIES THE NECESSARY BASEMENT HEIGHT AND THE DESIGN HAS BEEN CERTIFIED BY THE BOARD-APPROVED INSPECTION AGENCY.