M-SERIES

SUBMITTAL DATA: MSZ-FH15NA

15,000 BTU/H WALL-MOUNTED INDOOR UNIT FOR MXZ-C MULTI-ZONE HEAT-PUMP SYSTEMS

Job Name:	
System Reference:	Date:

Inspections Division
Date: 05/31/17

Indoor Unit: MSZ-FH15NA

Wireless Remote Controller

ACCESSORIES:

Indoor Unit

- ◻ Condensate Pump (BlueDiamond X87-711/721; 115/230V)
- ◻ Condensate Pump (Sauermann SI30-115/230; 115/230V)
- ◻ Replacement Platinum Deodorizing Filter (MAC-3000FT-E)
- ◻ Replacement Anti-allergy Enzyme Filter (MAC-2330FT-E)

Controls

- ◻ Wireless Controller (MHK1)
- ◻ Wired Remote Controller PAR-31MAA (Requires MAC-333IF-E)
- ◻ Wireless Interface for kumo cloud™ (PAC-WHS01WF-E)
- ◻ Thermostat Interface (PAC-US444CN-1)

SPECIFICATIONS:

Rated Capacity*		
Cooling[1]	Btu/h / W	15,000
Heating at 47° F[2]	Btu/h / W	18,000

Rating Conditions per AHRI Standard:
[1] Cooling | Indoor: 80° F(27° C)DB / 67° F(19° C)WB; Outdoor: 95° F(35° C)DB / 75° F(24° C)WB
[2] Heating at 47° F | Indoor: 70° F (21° C)DB / 60° F (16° C)WB; Outdoor: 47° F (8° C)DB / 43° F (6° C)WB

For data on specific indoor units (all ducted, all non-ducted, and both ducted and non-ducted) combinations, see the MXZ Technical and Service Manual.

Applications should be restricted to comfort cooling only; equipment cooling applications are not recommended for low ambient temperature conditions.

Electrical Power Requirements		208 / 230V, 1-Phase, 60 Hz
Minimum Circuit Ampacity (MCA)	A	1
Blower Motor (ECM)	F.L.A.	0.67
Blower Motor Output	W	30
Field Drainpipe Size O.D.	In.(mm)	5/8 (15)

Airflow Rate (Lo - Med - Hi - Super Hi - Powerful)			
Cooling	DRY	CFM	225-262-304-355-411
	WET		194-225-261-305-354
Heating	DRY		201-254-317-394-497

Sound Pressure Level (Lo - Med - Hi - Super Hi - Powerful)		
Cooling	dB(A)	27-31-35-39-44
Heating		25-29-34-39-46

External Dimensions (H x W x D)	In.(mm)	12 + 11/16 x 36-7/16 x 9-3/16 (305 +17 x 925 x 234)
Net Weight	Lbs.(kg)	29 (12)
External Finish		Munsell 1.0Y 9.2 / 0.2

Refrigerant Piping (Flared)		
Liquid (High Pressure)	In.(mm)	1/4 (6.35)
Gas (Low Pressure)		1/2 (12.7)

Specifications are subject to change without notice.

© 2016 Mitsubishi Electric US, Inc.

DIMENSIONS: MSZ-FH15NA

Inspections Division
Date: 05/31/17

MSZ-FH15NA

Unit: inch

(MSZ-FH15/18NA/18NA2)

Piping	Insulation	ϕ1-7/16 O.D
	Liquid line	ϕ1/4 19-11/16 (Flared connection ϕ1/4)
	Gas line	ϕ3/8 16-15/16 (Flared connection ϕ1/2)
Drain hose		Insulation ϕ1-1/8 Connected part ϕ5/8 O.D

MITSUBISHI ELECTRIC
COOLING & HEATING

1340 Satellite Boulevard. Suwanee, GA 30024
Toll Free: 800-433-4822 www.mehvac.com

Specifications are subject to change without notice.

© 2016 Mitsubishi Electric US, Inc.