



**REFLECTED CEILING PLAN** 1/4"=1'-0" **A**

	1'-0" x 4'-0" LED TROFFER		EXTERIOR WALL FIXTURE
	2'-0" x 4'-0" LED LIGHT FIXTURE		SPEAKER
	DOWNLIGHT @ WALK-IN (BY WALK-IN MFR.)		12" EXHAUST FAN
	PENDANT FIXTURE		HVAC RETURN GRILLE
	DOWNLIGHT		HVAC SUPPLY DIFFUSER
	EMERGENCY LIGHTS		HVAC PERFORATED SUPPLY DIFFUSER
	EXIT LIGHT (WALL MOUNTED)		BACK DOOR SECURITY STROBE LIGHT
	EXIT LIGHT (CEILING MOUNTED)		EXTERIOR CANOPY FLUORESCENT LIGHT

NOT USED 1/4"=1'-0" **F**

**CEILING SYMBOL LEGEND** **E**

**DIMENSIONS:**  
A. ALL DIMENSIONS ARE TO FACE OF FINISH U.O.N.

**CEILING FINISHES:**  
A. REFER TO ROOM FINISH SCHEDULE (SHT A7.2) FOR CLG. FINISHES.

**SUSPENDED CEILING:**  
A. ACOUSTICAL PANEL INSTALLATION: INSTALL ACOUSTICAL PANELS WITH EDGES IN CLOSE CONTACT WITH METAL SUPPORTS AND IN TRUE ALIGNMENT.  
B. ALLOWABLE VARIATIONS FROM FLAT AND LEVEL SURFACE: 1/8" IN 10'-0" MAX.  
C. ALLOWABLE VARIATIONS FROM PLUMB OF GRID MEMBERS: AS CAUSED BY ECCENTRIC LOADS, 2" MAX.  
D. INSTALL SYSTEM AFTER MAJOR ABOVE CLG. WORK IS COMPLETE. COORD LOCATIONS OF HANGERS WITH RELATED WORK.  
E. SEE SPECS FOR ADDITIONAL INFORMATION.

**GYPSUM BOARD CEILING:**  
A. SUBSTRATE SHALL BE 1/2" THICK GYP BD.  
B. ACOUSTICAL SEALANT: APPLY TO GYP. BD. PANELS AS INDICATED IN SPECS.  
GYP. BD. FINISHING AND DECORATING: REFER TO DWGS FOR TEXTURE AND FINISHES.

**ELECTRICAL:**  
A. SEE ELECT. DWGS. FOR FIXTURE SCHED.

**REFLECTED CEILING PLAN NOTES** **D**

- 1 CEILING GRID STARTING POINT.
- 2 BULKHEAD @ 8'-0" A.F.F.
- 3 NON-INSULATED BUNDLED SYRUP LINES FOR DRINK SYSTEM. SEE SCOPE OF WORK. SEE DETAIL 17/A6.4.
- 4 6" DIA PVC STUB THROUGH CEILING. SEE DETAIL 18/A6.4.
- 5 HOOD.
- 6 NEW REGISTERS AND GRILLS. (TYP. AT DINING, RESTROOMS, VESTIBULE AND OFFICE).
- 7 DRIVE THRU CANOPY.
- 8 DOWNLIGHT - CENTER IN CEILING TILE.
- 9 MENU BOARD. SEE SCOPE OF WORK.
- 10 MENU BOARD BULKHEAD - BOTTOM OF SOFFIT AT 7'-0" A.F.F. / SEE DETAIL 1/A6.4.
- 11 PRE-FABRICATED & PRE-FINISHED SOFFIT BY 3RD PARTY VENDOR. PROVIDE CLG. TILES ABOVE SOFFIT. (D-549) (OPTIONAL)
- 12 SPEAKER, CENTER IN CEILING TILE PANEL.
- 13 PENDANT LTG - CENTER OVER TABLE TOP (TYP). COORDINATE WITH DECOR FIELD INSTALLATION.
- 14 EXTERIOR WALL LIGHT FIXTURES, SEE ELEVATIONS AND ELECT. DWGS.
- 15 UTILITY CHASE BY 3RD PARTY VENDOR TO CEILING.
- 16 EMERGENCY DUAL HEAD FIXTURE. SEE ELECT. DWGS.

- 17 SECURITY STROBE LIGHT, REFER TO ELECT. DWGS.
- 18 FAN COIL FOR WALK-IN.
- 19 6" x 6" 18 GA. STAINLESS STEEL CHASE ALONG WALL FOR ICE MACHINE REFRIGERANT LINES: 6" ABOVE CEILING TO TOP OF ICE MACHINE.
- 20 ALERT LIGHT BOX FOR 3-COMP POWER SOAK MOUNTED AT C.L. OF BOX 7'-11" AFF
- 21 SECURITY CAMERA, REFER TO ELECTRICAL DRAWINGS.
- 22 ALIGN BOTTOM OF LIGHT FIXTURE MOUNTING PLATE WITH EIFS REVEAL / CHANGE IN EIFS THICKNESS.
- 23 ARCHITECTURAL ALUMINUM VALANCE BY VENDOR. SEE BUILDING ELEVATIONS.
- 24 3 ROWS OF LED LIGHTS BEHIND SLAT WALL. SEE BUILDING SECTIONS.
- 25 SLATWALL SYSTEM BY VENDOR. SEE BUILDING ELEVATIONS.
- 26 STAINLESS STEEL SYRUP CHASE ON WALL. SEE DETAIL 19/A6.4.
- 27 WATER INLET CHASE FOR CHEESE MELTER SCREWED TO HEATED AIR SCREEN.
- 28 NEW L.E.D. RECESSED LIGHTING FIXTURE BY CANOPY MANUFACTURER.
- 29 NEW ROOF ACCESS.

**KEY NOTES** **B**



07/14/16

15034.000

CONTRACT DATE: 07.06.2016  
BUILDING TYPE: CONVERSION  
PLAN VERSION: FEBRUARY 2015  
SITE NUMBER: XXX-XXX  
STORE NUMBER: XXXXX

**TACO BELL**  
1363 WASHINGTON AVE.  
PORTLAND, ME



**REFLECTED CEILING PLAN**

**A7.1**

PLOT DATE: