



1 PROPOSED REFLECTED CEILING PLAN
 SCALE: 1/8"=1'-0"

PROJECT SCOPE



PROJECT NORTH



ADD Inc

311 SUMMER STREET BOSTON, MA 02210 617.234.3100

ISSUANCES

No.	Description	Date
1	ISSUED FOR PERMIT	12/23/08

Checked by: JE

Proposed
 Reflected
 Ceiling Plan
 Floor 2

Drawing Scale: 1/8"=1'-0"

Job No. 08121.00

IA-202

REFLECTED CEILING PLAN LEGEND

TYPICAL SYMBOL NOMENCLATURE

R DENOTES RELOCATED FIXTURE
 ALL ARE FROM ADJACENT AREAS
 COORDINATE WITH EXISTING CONDITIONS

N DENOTES NEW FIXTURE

NEW 2 X 2 SUSPENDED
 CEILING GRID SYSTEM

EXISTING 2 X 2 SUSPENDED
 CEILING GRID SYSTEM
 TO REMAIN

GWB CEILING/SOFFIT

CEILING HEIGHT KEY
 CEILING HEIGHT - AFF
 CEILING TYPE

1' X 4' FLUORESCENT STRIP

2' X 2' FLUORESCENT

2' X 4' FLUORESCENT

WALLWASHER

DOWNLIGHT

EMERGENCY LIGHT
 BATTERY POWERED
 WALL MOUNTED

OCCUPANCY SENSOR

EXIT SIGN
 ARROWS INDICATE DIRECTION

EXIT SIGN - WALL MOUNTED
 ARROWS INDICATE DIRECTION

SMOKE DETECTOR

SPRINKLER

SUPPLY DIFFUSER

RETURN AIR GRILLE

N.I.C.

REFLECTED CEILING PLAN NOTES

1. ALL ACT CEILINGS TO BE ETR @ 8'-6" AFF U.O.N. VERIFY THIS DIMENSION WITH THE PERIMETER WINDOW HEAD CONDITION AND REVIEW WITH THE ARCHITECT/DESIGNER PRIOR TO START OF CONSTRUCTION.
2. ALL DOWNLIGHTS, WALLWASHERS, SMOKE DETECTORS, SPRINKLER HEADS, EXIT SIGNS, ETC. TO BE CENTERED IN CEILING TILE, U.O.N.
3. WALLWASHERS AND DOWNLIGHTS TO BE CENTERED, IN BOTH DIRECTIONS, IN ALL GWB SOFFITS, U.O.N.
4. ALL DIMENSIONS OF FIXTURES, DEVICES, SPRINKLER HEADS, ETC. ARE TO CENTERLINE OF FIXTURE, U.O.N. WHERE ITEMS ARE IN LINE, ALIGN CENTERLINE OF ITEMS OR GROUP OF ITEMS TO ALIGN, U.O.N.
5. ACT CEILING TO BE CENTERED IN ALL ROOMS, U.O.N. REFER TO CEILING LAYOUT FOR GRID LINE OR TILE TO BE CENTERED. CUT CEILING TILES TO BE 6" MINIMUM (NOTIFY ARCHITECT/DESIGNER IF LESS, PRIOR TO CONSTRUCTION).
6. ALL MEP-FP DEVICE LOCATIONS NOT SHOWN ON DRAWINGS, OR IN CONFLICT WITH MEP-FP DRAWINGS, ARE TO BE COORDINATED WITH ARCHITECT PRIOR TO INSTALLATION.
7. CONTRACTOR TO COORDINATE LOCATIONS OF ALL CEILING ELEMENTS AND PROVIDE COMPLETE COORDINATION DRAWINGS FOR THE ARCHITECT AND ENGINEER'S REVIEW FOR APPROVAL PRIOR TO CONSTRUCTION.
8. CONTRACTOR TO VERIFY ALL PENDANT FIXTURE HEIGHTS AND LOCATIONS WITH ARCHITECT PRIOR TO INSTALLATION.
9. GC TO SALVAGE ALL REMOVED EXIT SIGNS FOR POSSIBLE REUSE.
10. ALL GWB CEILINGS/HEADERS SHALL BE PAINTED, CEILING WHITE.

REFLECTED CEILING PLAN KEYNOTES

1. INSTALL NEW ACT CEILING GRID SYSTEM & TILES TO MATCH EXISTING IN PROFILE, PATTERN & FINISH.