#### City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Phone: Permit No: Location of Construction: Owner: 797-6913 Anthony Bellino 84 Vermont Ave. BusinessName: Lessee/Buyer's Name: Phone: Owner Address: SAA Përmit Issued: Phone: 756-2109 or 756-2109 Contractor Name: Address: Il Bowdoin Drive, Falmouth, ME \*\*Dean Cressey PERMIT FEE: COST OF WORK: Proposed Use: Past Use: \$ 3,000 \$ 35.00 **FIRE DEPT.** □ Approved INSPECTION: Same 1-Family Use Group: Type: ☐ Denied CBL:405A-F-030 Signature: // Signature: Zoning Approval: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Proposed Project Description: Approved Action: Special Zone or Reviews: Replace and repair existing deck and add 8x24 addition to deck Approved with Conditions: ☐ Shoreland 🍐 П □ Wetland Denied ☐ Flood Zone □ Subdivision Date: Signature: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: June 28, 1999 20 Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. 2. ☐ Conditional Use ☐ Interpretation Building permits are void if work is not started within six (6) months of the date of issuance. False informa-3. ☐ Approved tion may invalidate a building permit and stop all work.. ☐ Denied \*\*\*\*\*Call for Pick Up Dean Cressey Historic Preservation 878-0190 or 756-2109 □ Not in District or Landmark Does Not Require Review ☐ Requires Review PERMIT ISSUED Action: WITH REQUIREMENTS ☐ Appoved CERTIFICATION ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit June 28, 1999 DATE: PHONE: ADDRESS: SIGNATURE OF APPLICANT

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

CEO DISTRICT

PHONE:

BUILDING PERMIT REPORT						
	1 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
	DATE: 30045e 17 ADDICESS. O COLOR TO DE GECK					
REASO	REASON FOR PERMIT: Replace & repair cleck - 8x24 addition 10 gock					
BUILDI	INGOWNER: An Thon Y BUILING					
PERMI	TAPPLICANT: Dean (rossey					
USE GI	O CONSTRUCTION TYPE 7					
002 02	CONDITION(S) OF APPROVAL					
	rmit is being issued with the understanding that the following conditions are met:					
This per	X/47 X11 X13 429 X 2 2 4 3 4 3 1					
Approv	red with the following conditions: $\frac{2}{2}$					
¥ 1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.  Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A					
<b>√</b> 2.	Before concrete for foundation is placed, approvals from the Bossephane 24 hour notice is required prior to inspection)  24 hour notice is required prior to inspection)					
	Foundation drain shall be placed around the perimeter of a foundation drain shall be placed around the footing. The					
. <i>3</i> .	areant material that masses through a No. 4 sieve. The drain is not					
	At inforce shall be such that the bottom of the than is not any and filter membrane material. Where a than					
	less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filed inches above the top of the footing. The top of perforations tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations and					
	at all he protected with an approved filter memorate minorities.					
. 4. 1	shall be protected with an approved met intermediate. Section 1813.5.2 shall be covered with not less than 6" of the same material. Section 1813.5.2 Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from comers of foundation and a Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from comers of foundation and a Foundations anchors shall be a minimum of ½".					
4.	Foundations anchors shall be a minimum of 7. In diameter,					
	maximum 6' o.c. between bolts. (Section 2303.17)					
5.	Waterproofing and dampproofing shall be done in the Waterproofing and dampproofing shall be to write the Precaution must be taken to protect concrete from freezing. Section 1908.0  Precaution must be taken to protect concrete from freezing. Section 1908.0					
6.	Waterproofing and disapproved to protect concrete from freezing. Section 1908.0  Precaution must be taken to protect concrete from freezing. Section 1908.0  It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the					
7.	and any analysis are maintained.					
8.	Director garages located beneath habitable fooms in occupancies in the property of the registing rating. Private garages attached					
	1 fro partitions and floor/celling assembly which are a by means of 72 mon					
	spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour life residual states area by means of ½ inch spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour life residual states area by means of ½ inch spaces and the attic area by means of ½ inch spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum b					
	gypsum board or the equivalent applied to the gatago mental and a serious board or the equivalent applied to the gatago mental and a serious process and a serious process and a serious process and a serious process are process.					
	Section 407.0 of the BOCA National Mechanical All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code.					
9.	o 1./1002) Chapter 1/ & NFFA 411					
10	Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the original surfaces for the Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the original surfaces for the Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the original surfaces for the Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the open sides of elevated walking surf					
X11:	Our death of Handrails' A guardrant system is a system of the system of					
	- 6 minimizing the nossibility of all avoidoning and open Dalking structures					
	open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass intough any openments open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass intough any openments open guards shall have a minimum of 3e4" but not more than 38". Use Group R-not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1					
	not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 364 but not hot have an ornamental pattern that would provide a ladder effect. (Handrails shall have a circular cross section with an outside diameter of at least 1 3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 3 shall not be less than 30", but not more than 38".) Handrails shall be on both sides of stairway. (Section 1014.7)					
12.	1/4" and not greater than 2. (Sections 1992)  Headroom in habitable space is a minimum of 7'6". (Section 1204.0)  Headroom in habitable space is a minimum of 7'6". (Section 1204.0)  Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 '/4" maximum rise. All other Use Group minimum 11" tread,					
12.	Stair construction in Use Group R-3 & R-418 a fluthment 2					
	## ###################################					
14.	boodroom in all parts of a stativary shall not be a stativary shall not					
15.	Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operated knowledge or separate tools. approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. All					
	TTT					
	egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 hours. (Section 1018.6) minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6) minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)					
16.						
10.	Each apartment shall have access to two (2) separate, remote and approved included of Section 1010.1) from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1) from the apartment to the building exterior with construction having a fire rating of at least one (1) hour, including fire doors with self closer's.					
17.	from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1) from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1) All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's.  All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's.					
	(Over 3 stones in neight requirements are the construction including fire doors and ceiling, or by providing automatic  The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic  The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic					
18.	The boiler shall be protected by enclosing with (1) hour and a constant of the City's					

All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's

Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be

19.

installed	and maintained at the following locations):
•	In the immediate vicinity of bedrooms

In all bedrooms

• ... In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall maintained to NFPA #13 Standard.
- 23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
- 24. Section 25-135 of the Municipal Code for the City of Portland states, 'No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year'.
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 28. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
  - Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- Please read and implement the attached Land Use Zoning report requirements.—This property is At The MAX. Lot Cover AgeBoring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.

  Add this

  Glass and glazing shall meet the requirements of Chapter 24 of the building code.
  - The proposed Pier Foundation For The New deck Shall be placed on a Footing with anchor between The Two-Also, a fastener shall be used From pier To Framing.

A same Houses Milding Inspector

Id. Morfougall, PFD Marge Sehmuckal, Zoning Administrator

PSH 12-14-98

36.

<sup>\*\*</sup>On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

	Applicant: Dem Cressey	Date:	7/2/19			
	Address: 84 Vernat Ave		405 A-F-	<del>50</del>		
	NANCE					
	Date - to S					
	Zone Location - R-3					
(	Interior or corner lot -	W 11	.1			
	Proposed Use Work - Replace old deel - Add New					
	Servage Disposal - Cul					
	Lot Street Frontage -					
	Front Yard - WA					
Rear Yard - 25' Fely - 25' Show Side Yard - Votory Deck B' Teg H Slow						
	Width of Lot -					
	Height -			/		
	Lot Area - 7,650		2 (4)	ŕ		
Lot Coverage/Impervious Surface - 25% (9/2.5)						
	Area per Family -			1		
	Off-street Parking -	7.4 × 47 -	- 1008	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
	Loading Bays -	14×24	_ 336	MAX		
	Site Plan -	12 Cx 74	- = 324			
	Shoreland Zoning/ Stream Protection -	13.5 1 20	- 240			
	Flood Plains -	1000	(1908)			

### THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

# **Building or Use Permit Pre-Application** Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

84 Vermont AUF

Location/Address of Construction:

provisions of the codes applicable to this permit.

Signature of applicant:

Tax Assessor's Chart, Block & Lot Number	Owner:	Telephone#:						
Chart# 40514 Block# F Lot# 630	Anthony Bellino	7976913						
Owner's Address:	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee 6						
84 Vermont Ave.		\$3,000 \$35						
Proposed Project Description:(Please be as specific as possible)	Proposed Project Description (Please be as specific as possible)							
Repair and Replace pristing Deck and Add 8x24 Addition to decembractor's Name, Address & Telephone Rec'd By:								
Contractor's Name Address & Telephone	√ , Red	d By:						
Dean Cressey 11 Bowdor	Dean Cressey 11 Bowdoin Dr Falmonth 8780190							
Separate permits are required for Inte	ernal & External Plumbing, HVAC and	Electrical installation.						
<ul> <li>All construction must be conducted in complia</li> </ul>	nce with the 1996 B.O.C.A. Building Code as	s amended by Section 6-Art II.						
	ted in compliance with the State of Maine Plu							
	th the 1996 National Electrical Code as amer							
•HVAC(Heating, Ventilation and Air Condit	44 .	. 11-5 6						
You must Include the following with you a	ipplication:	i monti						
1) A Copy of You	application:  r Deed or Purchase and Sale Agreem  our Construction Contract, if availab  Plot Plan (Sample Attached)	ient glassin Plot						
2) A Copy of yo	our Construction Contract, if availab	le of fee						
3) A I	Plot Plan (Sample Attached)	fa 6 (13)						
if there is expansion to the structure, a con	npiete piot pian (Site Pian) must include	e:						
• The shape and dimension of the lot, all ex	• The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual							
property lines. Structures include decks po	orches, a bow windows cantilever sections and	oof overhangs, as well as, sheds,						
	pools, garages and any other accessory structures.							
Scale and required zoning district setbacks								
property lines. Structures include decks potenes, a bow windows cantilever sections and four overhangs, as well as, sheds, pools, garages and any other accessory structures.  • Scale and required zoning district setbacks  4) Building Plans (Sample Attached)								
4) Building Plans (Sample Attached)								
A complete set of construction drawings showing an of the following elements/on/construction/you								
<ul> <li>Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)</li> <li>Floor Plans &amp; Elevations</li> </ul>								
Window and door schedules								
• Foundation plans with required drainage and dampproofing								
• Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas								
equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.								
	Certification	*						
I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record								
and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable								

laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1.000.00 construction cost thereafter.

Date: (2)



Inspection Services Michael J. Nugent Manager

Department of Urban Development Joseph E. Gray, Jr. Director

#### CITY OF PORTLAND



## Building or Use Permit Application Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

As an applicant for a building permit, you are about to enter into a relationship with our Office. We welcome any questions, comments or suggestions that will make the process more efficient. Attached you will find an application and some samples of the submissions you will provide at application time. Please read <u>ALL</u> of the information and if you need any further assistance please call 874-8703 or 874-8693.

28' For Front of house
House 42 x 24
garage 14 x 24

