Reviewed for Code Compliance
Inspections Division
Approved as submitted
Date: 05/24/16

HZ106-A1 One Story or Top of Two Story Issued: 3/3/14

Distance from Vert BWL 1 to Vert BWL 2 = 34 ft

	Input Panel Lengths Below, ft							
	Exterior Horizontal Braced Wall Lines				Exterior Vertical Braced Wall Lines			
	Horizontal BWL 1		Horizontal BWL 2		Vertical BWL1		Vertical BWL2	
BW Type:	WSP		WSP		WSP		WSP	
	Actual	Effective	Actual	Effective	Actual	Effective	Actual	Effective
	11.464	11.464	5.432	5.432	13.583	13.583	16.25	16.25
	7.969	7.969	3.901	3	9.219	9.219	3.75	3
	4.74	4.74	3.901	3	0	0	0	0
	0	0	3.37	2.25	0	0	0	0
	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0
Lp =	24.173 ft		13.682 ft		22.802 ft		19.25 ft	
Lr =	4.902 ft		4.902 ft		6.302 ft		6.302 ft	
Meets Requirements?	OK		OK		OK		OK	
Horizontal Joint Blocking Required ?	NO		NO		NO		NO	

	Interior Vertical Braced Wall Lines, Method GB					
	N/A		N/A		N/A	
BW Type:	GB		GB		GB	
	Actual	Effective	Actual	Effective	Actual	Effective
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
Lp =	0 ft		0 ft		0 ft	
Lr =	0.000 ft		0.000 ft		0.000 ft	
Meets Requirements?	N/A		N/A		N/A	
Horizontal Joint Blocking?	N/A		N/A		N/A	

Note: All GB BW panels must have GYP on both sides of the wall section. All WSP BW panels must have GYP on the other side of the wall section.

(Table 2)