


W8X18 HEADER BEARING ON 3"O SCHD. 40 PIPE COLUMN @ EACH END.
L3X3X1/8" CLIPS W/ (2) 3/4"O A325 BOLTS TO WEB OF HEADER
12 GAUGE PAN STAIR W/ 1-1/2" MIN. CONCRETE TREADS

DOUBLE 16 GAUGE CLIP ANGLE HEADER TO JOIST CONNECTION FASTENED W/ (4) #10 TEK SCREWS - TYP.

BALLOON FRAMED STRUCTURAL UNIT SEPARATION WALLS - SEE ARCHITECTURAL FOR FINISH DETAILS - TYP.

ALL FLUSH HEADERS TO BE DOUBLE JOIST BEAMS W/ TOP TRACK TYP.

JOISTS BEAR ON (N) METAL STUD WALL PER SECTION



SECOND FLOOR FRAMING PLAN

NOTES:
1. 2" CONCRETE TOPPING OVER METAL DECK - TYP.
2. SEE GENERAL NOTES FOR MORE INFO. - TYP.

SCALE 1/8"=1'-0"

FRAMING PLAN SYMBOLS KEY	
□	POST
○	STEEL COLUMN
(X)	NUMBER OF METAL STUDS IN POST BELOW
A	COLUMN ABOVE THIS LEVEL
C	COLUMN CONTINUOUS THROUGH THIS LEVEL
/E/	EXISTING COLUMN BELOW
←	JOIST BEARING
→	CONTINUOUS JOIST WITH INTERMEDIATE BEARING
↔	FLUSH FRAMED JOIST BEARING WITH HANGER
▬	METAL STUD BEARING WALL BELOW
▨	SHEAR WALL
⌈X⌋	NUMBER OF TRIM STUDS UNDER HEADER
⌈X⌋K	NUMBER OF KING STUDS ADJACENT TO HEADER

COORDINATION / REVIEW DRAWINGS
NOT FOR CONSTRUCTION