


7½- TO 12½-TON THREE-PHASE  
PACKAGED GAS/ ELECTRIC  
UP TO 11.3 EER / 80% AFUE

Cooling Capacity:  
88,000 — 144,000 BTU/h  
Heating Capacity (Output):  
168,000 BTU/h



### ■ Contents

Nomenclature.....	2
Product Specifications.....	4
Expanded Cooling Data .....	8
Airflow Data.....	16
Dimensions .....	20
Wiring Diagrams .....	24
Accessories .....	36

### ■ Standard Features

- TuffTube™ tubular heat exchanger
- High-efficiency scroll compressors
- Two-stage heating and cooling
- Copper tube / aluminum fin coils
- Power block for field wiring
- High-capacity, steel-cased filter drier
- Single-point entry
- 24-volt terminal strip
- Convertible airflow orientation
- Built-in filter rack with standard 2" filters
- Complies with California Low NOx emissions standards
- Units meet the performance outlined in Table 6.8.1A of ASHRAE Standard 90.1-2010
- AHRI Certified; ETL Listed

### ■ Cabinet Features

- Heavy-gauge, galvanized-steel cabinet with UV-resistant powder-paint finish
- Full perimeter rail
- Sloped drain pan
- Easy to service



\* Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com).