			ſ	PERMIT ISSUE	D		
	aine - Building or Use		1 1	it N : Issue Date:	CBL:		
	4101 Tel: (207) 874-8703	Fax: (207) 874-87	16	01 112 FP 2 7 2001	422 B051001		
Location of Construction: Owner Name			Owner Address:		Phone:		
378 Presumpscot St Crandall Real				PORTLA	207-761-2092		
Business Name: Contractor Name		:	Contrac		Phone		
n/a Aerp Htv Inc.		378 Presumpscot St Portland			2077612092		
Lessee/Buyer's Name n/a	Phone:		Permit Type:  Alterations - Commercial		Zone:		
Past Use:			Permit		CEO District:		
		Office build out		\$156.00 <b>/</b> \$21,700.0	1		
	991111111111111111111111111111111111111		FIRE D	FIRE DEPT: Approved INSPECTION:			
Proposed Project Description				Approved	Type: 34		
Office Build Out - A	Proposed Project Description: Office Build Out - Assessory to Mfg use						
Office Build Out			Signatur	TRIAN ACTIVITIES DISTRIC	TO TOMAL I I YU		
				ved w/Conditions benied			
:			Signatu	re:	Date:		
Permit Taken By:	Date Applied For: 09/07/2001		Zoning Approval				
This permit application does not preclude the Applicant(s) from meeting applicable State and Federal Rules.				Zoning Appeal	Historic Preservation		
				☐ Variance	Not in District or Landmar		
2. Building permits do not include plumbing, septic or electrical work.		Wetland ASSESS Miscellaneous		Miscellaneous	Does Not Require Review		
3. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work		Flood Zone 10 1	Flood Zone to Mfg Conditional Use		Requires Review		
		☐ Site Plan ☐ Appr  Maj ☐ Minor ☐ MM ☐ ☐ Denie		Interpretation	Approved		
				Approved	Approved w/Conditions		
	Denied			Denied			
		Date: 9/26/6		Date:	Date:		
				V	PERMIT ISSUED WITH REQUIREMENTS		
		CERTIFICATI	ON				
jurisdiction. In addition, i	the owner to make this appli if a permit for work described	med property, or that t ication as his authorize I in the application is i	he propo d agent a ssued. I c	and I agree to conform to a certify that the code official	the owner of record and that ll applicable laws of this il's authorized representative n of the code(s) applicable to		
			-··-				
SIGNATURE OF APPLICANT		ADDRES	S	DATE	PHONE		

## All Purpose Building Permit Application

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Total Square Footage of Proposed Structu	ure Square Footage of Lot	95,138
Tax Assessor's Chart, Block & Lot Chart# 422 Block# 8 Lot# 5/	Owner: (randal/ Realty LLC:	Telephone: 207-76/-2092
Lessee/Buyer's Name (If Applicable)	Applicant name, address & telephone: Craudall Realty UC 378 Prosumpscot Street BrHand, Maire 04/03	Cost Of 21, 720 00 Work: \$ 21, 720 00
If the location is currently vacant, what we Approximately how long has it been vacant.  Proposed use: Pre fibricated Comproject description: Minor office in	loset manufacturer	
205	gena ( )	
	Aero HtV Inc 377 Prosump fortland, the 04103 is ready: Pete Colland	<del></del>
Contractor's name, address & telephone: Who should we contact when the permit Mailing address: 378 Presumps cot 54	Aero Htv Inc 37) Production is ready: Pete Collard  UDED IN THE SUBMISSIONS THE PERMIT WE PERMIT.  ERMIT.  Comed property, or that the owner of record authorized agent. I agree to come this application is issued. I certify that the Code	Phone: 76(-2892  VILL BE AUTOMATICALLY  OUIRE ADDITIONAL  orizes the proposed work and that a conform to all applicable laws of this Official's authorized representative

	BUILDING PERMIT REPORT
	DATE: 13 September 200/ADDRESS: 378 PresumpscoT Street CBL: 422-13-45/
	REASON FOR PERMIT: Office FIX-UP-
	BUILDING OWNER: Crandall Realty L/C
	PERMIT APPLICANT: /CONTRACTOR for y HTV Inc.
	PERMIT APPLICANT: /CONTRACTOR for p HTV Inc.  USE GROUP: CONSTRUCTION TYPE: CONSTRUCTION COST: 21, 9/9. PERMIT FEES: 15/6/01
,	The City's Adopted Building Code (The BOCA National Building Code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
•	CONDITION(S) OF APPROVAL
	This permit is being issued with the understanding that the following conditions shall be met: 1 × 11 × 13 × 2 ( 23 1) × 24 26 29 29 20 23 12
K	1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.  2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."  3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The

3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2

4. Foundations anchors shall be a minimum of 12" in diameter, 7' into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17

5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete and masonry. Concrete Sections 1908.9-19.8.10/ Masonry Sections 2111.3-2111.4.

7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the

proper setbacks are maintained.

8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)

9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211

- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A, B.H-4, I-1, I-2, M, R, public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36 inches (914 mm) and not more than 42 inches (1067 mm). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ½" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7) R-3 (ONE & TWO FAMILY DWELLINGS) GUARD HEIGHT IS 36" MINIMUM.

Headroom in habitable space is a minimum of 7'6'. (Section 1204.0)

13. Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7 %" maximum rise.</u> All other Use Group minimum 11" tread, 7' maximum rise. (Section 1014.0)

14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

- 15. The Minimum required width of a corridor shall be determined by the most restrictive of the criteria trider section 1011.3 but not less then 36".
- 16. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)

17. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

18. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closure's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)

19. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

20. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In all bedrooms In each story within a dwelling unit, including basements 21. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0) 22. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard. 23. The Sprinkler System shall be installed and maintained to NFPA #13 Standard. 24. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999) 25. Section 25 - 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". 1 26. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services. 27. Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces & attics). 1/28. All electrical, plumbing and HVAC permits must be obtained by Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done. 29. All requirements must be met before a final Certificate of Occupancy is issued. 30. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1996). 31. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Separate paints Are required Code/1993). (Chapter M-16) (32.) Please read and implement the attached Land Use Zoning report requirements. 35. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code. 34. Bridging shall comply with Section 2305.16. 35. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0) 36. All flashing shall comply with Section 1406.3.10. 37. All signage shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999). offses, Building Inspector Et. McDougall, PFD Marge Schmuckal, Zoning Administrator

Michael Nugent, Inspection Service Manager

MMIN

PSH 10/1/00

\*This permit is here with issued, on the basis of plans submitted and conditions placed on these plans, any deviations shall require a separate approval.

···THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. (You Shall Call for Inspections)

\*\*\*\*ALL PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL, (AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000, DXF FORMAT OR EQUIVALENT.

\*\*\*\*\*CERTIFICATE OF OCCUPANCY FEE \$50.00

GENERAL RECEIPT

## CITY OF PORTLAND, MAINE

1	RIMENT	DATE	7/5	1
	VED FROM CO T	1	100 to 300	
3 S	1	, Dr	\	
<del></del>		,	<del>,</del>	
UNIT	ITEM	REVENUE CODE	DOLL/ AMOUI	AR NT
	Figure		156	<u>ი</u>
	seunit			
-				
	heef # 688	80	,-	
	CBF: 432	60	51	
			1	
			!	
☐ CAS	SH ☐ CHECK ☐ OTHER	TOTAL	155	 5U
DE OF!!	<u> </u>			
RECEIVE	GBF INFORMATION SYSTEMS BOX 878, PORTLAND, ME ON 104 (207	774 1400		

en de la companya del companya de la companya del companya de la companya del companya de la companya de la companya de la companya del companya de la companya del la companya

## Office Space Addition

ScopE OF WORK!

Existing 5,000 Sq. Ft. REHTAL SPACE EMPTY

Add 689 Sq. Ft. of Interior Office Space with A MEZZANINE FOR Above Storage.

To INClude AS follows:

1. RECEPTION AREA RO.
15 FELORIUS
2. OFFICE SPECES 10FE 10FW
1- Conference RM. 10. 15FM.
1. HAMDICAP BATH GREAGENS

1. 5-tonge Closet 5th 10th

tristing Space is Currently COVERED )
by Sprinkler System & Will CONTINUE
Throught NEW SPACES.

## Office Space Addition

ScopE OF WORK;

Existing 5,000 Sq. Ft. RENTAL SPACE EMPTY

Add 689 Sq. Ft. of Interior Office Space with A MEZZANINE FOR Above Storage.

To INCLUDE AS follows:

1. RECEPTION AREA 15 FELOFE


2. OFFICE SPACES 10FLOTE


1. Conference RM. 10. 15 FE.

1. HANDICAP BATH BATH

1. Stonge Closet 5FLOFE.

Dy Sprinkler System & will continue Thrucul New Spaces.





ELEVATION PLATE

ZXID JOIST

ETT (2) 2X4 TOP PLATES

ETT (2) 2X4 TOP PLATES

ETT (2) 2X4 TOP PLATES

ETT (2) 2X4 WALL STUD

Exterior - 36x48 Full Glass

INTERIOR RAISED FINIEL

3.3/0x6/8 L.H

1-3/0×6/8 R.H

1-26 + 6/8 R.H.

9 lite

1-3/0x6/8 Litt.