(4)3/4" Dia. GR36 A.Rods
Plate W=8" L=1'-1"
Elev.=100'-0"
Dim: A=1'-1 1/2" B=1'-0"

D2 (4)3/4" Dia. GR36 A.Rods
Plate W=8" L=11"
Elev.=100'-0"

D3 (4)3/4" Dia. GR36 A.Rods
Plate W=8" L=10"
Elev.=100'-0"

D4 (4)3/4" Dia. GR36 A.Rods
Plate W=8" L=1'-1"
Elev.=100'-0"

D5 (4)3/4" Dia. GR36 A.Rods
Plate W=8" L=1'-1"
Elev.=100'-0"

TYPICAL ANCHOR ROD PROJECTION

NOTE: 1" (25mm) PROJECTION ABOVE BOTTOM OF JAMB CLIP

JAMB 'EQ.' VALUES:

7" EQ = 2" 51mm, 8 1/2" EQ = 2 3/4" 70mm
10" EQ = 3 1/2" 89mm, 11 1/2" EQ = 4 1/4" 108mm

FRAMED OPENING DETAIL

TYPICAL COLUMN BASE PLATE DETAIL

1. CONCRETE, GROUT, ANCHOR RODS, AND ANY OTHER EMBEDDED ITEMS ARE TO BE FURNISHED BY OTHERS.
2. ANCHOR ROD DIAMETERS WERE DETERMINED BY ALLOWABLE SHEAR AND TENSION PER AISC SPECIFICATIONS (FY=36KSI). ANCHOR ROD LENGTH, EFFECTS OF EMBEDDED ANCHOR ROD EDGE DIMENSIONS AND METHOD OF TRANSFERRING FORCES FROM ANCHOR RODS TO FOOTINGS ARE TO BE DETERMINED BY OTHERS.
3. UNLESS OTHERWISE SPECIFIED, ANCHOR RODS ARE DETAILED WITH A PITCH AND GAGE OF 5 INCHES ASSUMING "CAST-IN-PLACE" ANCHOR RODS WITH "SNUG TIGHT" CONNECTIONS.
4. FOUNDATION MUST BE LEVEL, SQUARE AND SMOOTH. ANCHOR RODS MUST BE ACCURATELY PLACED AS SHOWN ON THIS DRAWING OR STEEL WILL NOT FIT.
5. THE BUILDER IS RESPONSIBLE FOR ACCURATE SETTING OF ANCHOR RODS WITHIN INDIVIDUAL COLUMN ROD GROUPS -TOLERANCE +-1/8". DIMENSIONS BETWEEN ANCHOR ROD GROUPS - TOLERANCE +-1/4". ERECTION OF STEEL COMPONENTS MUST BE STRAIGHT AND PLUMB PER MBMA CODE OF STANDARD PRACTICE.
6. DESIGN LOADS AND REACTIONS ARE FURNISHED IN THE REACTIONS REPORT.

D1 (4)3/4" Dia. GR36 A.Rods
Plate W=8" L=1'-1"
Elev.=100'-0"

CITY OF PORTLAND, MAINE — RESURGAM

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 06/10/13

STATE OF MAINE — CARL W. WALKER No. 5999 — LICENSED PROFESSIONAL ENGINEER — 03.14.13

3/14/13 DKR

THE VP ENGINEER'S SEAL APPLIES ONLY TO THE WORK PRODUCT OF VP AND DESIGN AND PERFORMANCE REQUIREMENTS SPECIFIED BY VP. THE VP ENGINEER'S SEAL DOES NOT APPLY TO THE PERFORMANCE OR DESIGN OF ANY OTHER PRODUCT OR COMPONENT FURNISHED BY VP EXCEPT TO ANY DESIGN OR PERFORMANCE REQUIREMENTS SPECIFIED BY VP.

THIS DRAWING, INCLUDING THE INFORMATION HEREON, REMAINS THE PROPERTY OF VP BUILDINGS. IT IS PROVIDED SOLELY FOR ERECTING THE BUILDING DESCRIBED IN THE APPLICABLE PURCHASE ORDER AND SHALL NOT BE MODIFIED, REPRODUCED OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR WRITTEN APPROVAL OF VP BUILDINGS.

THE GENERAL CONTRACTOR AND/OR ERECTOR IS SOLELY RESPONSIBLE FOR ACCURATE GOOD QUALITY WORKMANSHIP IN ERECTING THIS BUILDING IN ACCORDANCE WITH THIS DRAWING, DETAILS REFERENCED IN THIS DRAWING, ALL APPLICABLE VP BUILDINGS ERECTION GUIDES, AND INDUSTRY STANDARDS PERTAINING TO PROPER ERECTION, INCLUDING THE CORRECT USE OF TEMPORARY BRACING.

VP Buildings
3200 Players Club Circle Memphis TN 38125

REV	DATE	BY	DESCRIPTION

NTS

ANCHOR ROD PLAN - DETAILS

BUILDER	Patco
CUSTOMER	
LOCATION	Portland, Maine
PROJECT	Pack Edge
BUILDERS PO#	

VP BUILDINGS — VARCO PRUDEN — A BlueScope Steel Company
VPC VERSION: 2012.3d

JOB #	12-4084
DATE	3/14/2013
DRAWN/CHECK	COOP DC
PAGE	4

3/13/2013 14:51:51
FILENAME: Pack Edge addition BO
a division of BlueScope Buildings North America, Inc.