Location of Construction: 28 Wellstone Dr	Owner:	arl & Kathrya	Phone:	Permit N9 707
Owner Address: SAA Ptld, HE 04103	Lessee/Buyer's Name:	Phone: 874-0911	BusinessName:	PERMIT ISSUED
Contractor Name: Peter Chase	Address:	Phone	:	Permit Issued:
ast Use:	Proposed Use:	COST OF WORI \$ 300.00	K: PERMIT FEE \$ 25.0	o
Condo	Same	FIRE DEPT. □ A	Approved INSPECTION Use Group:	Type:
		Signature:	Signature:	Zone: CBL: 423-A-005
Proposed Project Description:		PEDESTRIAN A	CTIVITIES DISTRICT (and the summer and the second second
Extend Deck - Not to exc	caed esisting decks	Î	Approved Approved with Conditions: Denied	☐ Special Zone or Reviews: ☐ Shoreland ☐ Wetland ☐ Flood Zone
Permit Taken By: Kary Greeik	Date Applied For:	Signature:	Date:	☐ Subdivision☐ Site Plan maj ☐minor ☐mm ☐
 This permit application does not preclude the Building permits do not include plumbing, Building permits are void if work is not start tion may invalidate a building permit and start tion may invalidate a building permit and start tion. 	, septic or electrical work. rted within six (6) months of the date			Zoning Appeal □ Variance □ Miscellaneous □ Conditional Use □ Interpretation □ Approved □ Denied
		. Company of the second	PERMIT ISSUED WITH REQUIREMEN	Historic Preservation Not in District or Landmark Does Not Require Review Requires Review Action:
I hereby certify that I am the owner of record of authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonable	on as his authorized agent and I agree is is issued, I certify that the code office	sed work is authorized by the to conform to all applicable ial's authorized representati	e laws of this jurisdiction. It we shall have the authority	n addition, Denied
SIGNATURE OF APPLICANT SETT PAQUE	ADDRESS:	11 July 199 DATE:	PHONE:	
				•

COMMENTS P-20-92

Inspection Record

Date

Type

Foundation: _____
Framing: _____
Plumbing: _____
Final: _____
Other: _____

BUILDING PERMIT REPORT

DATE: 22 July 97 ADDRESS: 28 Wellstone DR.	
REASON FOR PERMIT: To extend deck	, i
BUILDING OWNER: PaqueTte	
CONTRACTOR: Peter Chase	
PERMIT APPLICANT: OWNEL APPROVAL: \$ 1 42 ×8 × 10	DENIED

CONDITION(S) OF APPROVAL

This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)

Precaution must be taken to protect concrete from freezing.

4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.

5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)

6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.

Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.

8. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.

Headroom in habitable space is a minimum of 7'6".

Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.

11. The minimum headroom in all parts of a stairway shall not be less than 80 inches.

12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.

13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.

14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.

15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.

All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

• In the immediate vicinity of bedrooms

In all bedrooms

7.

• In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and

I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
- 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 23. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 24. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
- 25. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.
- 26. All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade.

28.

 $\langle \gamma \rangle \langle \gamma \rangle \langle \gamma \rangle$

Chief of Code Enforcement

cc: Lt. McDougall, PFD Marge Schmuckal

27.

29.

BASIC GUIDELINES FOR DECK PERMITS

Materials needed to apply for permit:

.

- 1) Plot Plan A Bird's eye view of your property showing where all your buildings are located in relationship to the lot lines and each other. You need to show those distances (the front, rear and sides) in feet.
- 2) <u>Construction Plan</u> Cross Section. What dimensional lumber/materials are being used and what is their make-up?

The following check-off sheet can be used in most circumstances:

3) Fee - Based on cost of work labor/materials. 25.00 1st 1,000 worth of work, 5.00 each additional 1,000.

	<u>Foundation</u>		Frost wall,	min 4' below	w grade		
				min 4' below	w grade, 6" min bedrock		
			Other				
	<u>sill</u>	loss/Hon/3	Distance be	tween foundat	tion supports		
	Joist Size	***************************************	2x6	2x8	2x10		
	Joist Span						
	Distance Between Joists	_1/	16"oc	24"00	other		
	Decking			other/explai			
	Stair Construction		10" min tr	oad	3/4" max riser		
	Guard Height		36"	42"	•		
Guards shall be located along open-sided walking surfaces located 15 1/2" above the floor or below grade. Single family - min 36", all others 42", measured vertically above the leading edge of the tread or adjacent walking surface. BOCA 1005.5/1021.2							
	Balusters	1	under 4"		· · · · · ·		
	Open guards shall have ba sphere with a diameter of not have an ornamental pa	4" cannot	pass through	h any opening	Guards shall		



