## City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Phone: Permit No: Location of Construction: Owner: 773-4728 Chapman Corporation Owner Address: 100 Presupecot St Ptid Phone: BusinessName: Lessee/Buyer's Name: DEPT. OF BUILDING INSPECTION P.O. Box 10700.PTD.04104 PermETIK OF BORTLAND, ME Contractor Name: Hatt Cook Allied/Cook Const Phone: Address: 72-2888 P.O. Box 1396, Portland, ME OCT | 3 1998 **COST OF WORK:** PERMIT FEE: Proposed Use: Past Use: MFGR MYGR FIRE DEPT. Approved INSPECTION: Use Group: ☐ Denied Type: CBL: Zone: 425-A-002 Signature: Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) 2 new signs: remove & reinstall existing sign Approved Action: Special Zone or Reviews: Approved with Conditions: □ Shoreland Denied □ Wetland ☐ Flood Zone □ Subdivision Date: Signature: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: 10-6-98 Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. 1. □Miscellaneous Building permits do not include plumbing, septic or electrical work. □ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-□ Interpretation 3. □ Approved tion may invalidate a building permit and stop all work.. □ Denied Historic Preservation ■ Not in District or Landmark ☐ Does Not Require Review □ Requires Review Action: ☐ Appoved CERTIFICATION ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit ADDRESS: DATE: PHONE: SIGNATURE OF APPLICANT

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

PHONE:

CEO DISTRICT

11)/14	COMMENTS
LEST MESSAGE Ch MA	FT COOKS VOTGETANDER
ADVISED HIM TO	CACI FOM. ()
10-20-98 Stoped By Sitework M	induring Bet No sign yet (TR)
11-19-98 Sign in Place	Clase Permi
	Inspection Record  Type Date
	Type Date Foundation:
	Framing:
	Final: 5.5n Them (1000)

Other:

## **BUILDING PERMIT REPORT**

	: 8 OCT 98 ADDRESS: 125 PresumpscoT31-CBL 425-A-602
REAS	on for permit: 519175
	DING OWNER: Chapman, Corp.
	TRACTOR: Allied/Could Const.
PERM	IIT APPLICANT:
USE G	GROUP BOCA 1996 CONSTRUCTION TYPE
	CONDITION(S) OF APPROVAL
This F	Permit is being issued with the understanding that the following conditions are met:
	oved with the following conditions: 4 4 4
Appro	oved with the following conditions:
/ī	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
( <del>1.</del>	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services
2.	must be obtained. (A 24 hour notice is required prior to inspection)
2.5	Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing
_,_	not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches
	beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the
	bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The
	top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used,
	the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be
	protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or
2.6	crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
2.6	Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of
3.	foundation and a maximum 6 'o.c. between bolts. (Section 2305.17)  Precaution must be taken to protect concrete from freezing. Section 1908.0
3. 4.	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is
••	done to verify that the proper setbacks are maintained.
5.	Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from
	adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire
	resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from
	the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½
	inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
6.	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA
~	National Mechanical Code/1993). Chapter 12 & NFPA 211
7.	Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's
8.	building code.  Guardrails & Handrails: A guardrail gustam is a gustam of building components leasted most the open sides of clausted.
ο.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower
	level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-
	1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such
	that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that
	would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be
	less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at
	least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section
	1014.7)
9.	Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
10.	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group
11	minimum 11" tread. 7" maximum rise.( Section 1014.0 )
11.	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8") 1014.4

- 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Table 302.1.1
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
- 24. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- 26. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 28. Please read and implement the attached Land Use-Zoning report requirements.
- 29. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.3. of the City's building code.

30. 31.	Glass and glazing shall meet the requirements of Chapter 24 of the building code.
32.	
<i>J</i>	
33.	

Samuel Hoffses, Building Inspector

cc: Lt. McDougall, PFD

Marge Schmuckal, Zoning Administrator

## THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

in the interest of processing your application in the quickest possible manner, please complete the information below for a Built

NOTES-Myou of the property owner ower real estate or personal property taxes or user charges on ANY PROPERTY

Location/Addressof Construction (Include Position of Bullsing):	125 Presumpscot St	The state of the s
Total Square Footage of Proposed Structure N/A	The state of the s	reet
Tax Axiessor's Cliait, Block & Lat Number		A
Chan# 425 Blook# A Low 2	Owner: Chapman Corporation	Tolephone4: 773-4728
Cwner's Address: P.O. BOX 10700, PTD, 04104	Lesser-Buyer's Name (If Applicable)	Cort Of Work:
125 Presumpscot St.,Ptd		\$ <sub>N/A</sub> \$
Proposed Project Description:(Please he as specific as possible)		-1/21
2 new signs; I removed and n  Commeter Name, Address Tolophone Contact Ma  Allied (Cook Cook Tolophone Contact Ma		
TOUR CONSTRUCTION, P.O.	Box 1396, Portland, M	E 04104 Rec'd B
Cincor Die: MFGR	Proposed Use: ME'GR	
"All plumbing must be conduct "All Electrical Installation must comply with "EVAC(Heating Rentillation and Ale Conduction and A	th the 1996 National Electrical Consen	ode as a present d by Section 6-1
All plumbing must be conduct  All Electrical Installation must comply wit  *EVAC(Heating, Sentillation and Air Condition ou must include the following with you application:  1) ACopy of You  2) A Copy of Your form with the senting of the following with your application:  (inor or Major site plan review with the senting of the senting	the discompliance with the State of Maith the 1996 National Electrical Confessioning) installation must comply with our Deed or Purchas and Sale Agreemyour Construct of Contract, if available A Plot Phin/Site Plan	ode as a positive by Section 6-Art III the 1993 BOCA Mechanical C ent  C PORILAND, ME  OF PORILAND, ME
All Electrical Installation must be conduct  All Electrical Installation must comply with  AVAC(Heating, Sentilliation and Air Condition  I) ACopy of Your must include the following with you application:  I) ACopy of Your condition of Major site plan review will a required for the becklist outlines the minimum standards for a site plan to the complete set of construction drawings showing and Cross Sections wiferaming downs (including Figor Plans & Elevations)	the discompliance with the State of Maisting the 1996 National Electrical Code of ioning) installation must come with our Deed or Purchase and Sale Agreem your Construction Contract, it available to the Man/Site Plan is above proposed projects. The maches in.  4) Building Plans on decuments must be designed by a few of the Mandal of the Contract of	ode as a positive by Section 6-Art III the 1993 BOCA Mechanical Control of Portland, ME  OCT 6 1998  egistered design professions.
All Electrical Installation must be conduct  All Electrical Installation must comply with  AVAC(Heating, Sentillation and Air Condition  I) ACopy of Your must include the following with you application:  I) A Copy of Your condition of Major site plan review will be required for the becklist outlines the minimum standards for a site plan to the complete set of construction drawings showing and complete set of construction drawings showing and cross Sections wiferancing decays (including	the discompliance with the State of Maistin the 1996 National Electrical Code of ioning) installation must come, with our Deed or Purchase and Sale Agreem your Constructor Contract, if available 3) A Plot Phin/Site Plan is above proposed projects. The anacher in.  4) Building Plans can decaments must be designed by a fithe following elements of construction proches, decks w/ rallings, and accessor dampers for any specialized equipment a or other types of work had may require a	ode as a positive by Section 6-Art III the 1993 BOCA Mechanical Control of the 1993 BOCA Mechanical Control of 1998  ent

Building Permit Fee: \$25,00 for the lat \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter. Additional Site review and related fees are attached on a separate addendum