Location of Construction:	Owner:		Phone:	Permit No: 9 7 0 7 0 0
120 Presumpscot St	Boulanger,			970700
Owner Address: SAA Ptld, ME 04103	Lessee/Buyer's Name:	Phone: 772-3019	BusinessName:	PERMIT ISSUED
Contractor Name: Owner	Address:	Phone:		Permit Issued:
Past Use:	Proposed Use:	COST OF WORK: \$ 1,000.00	PERMIT FEE: \$ 25.00	Jul - 3 1997
2-fam	Same	FIRE DEPT. □ Ap	nied Use Group: Typ	CITY OF PORTLAND
		Signature:	BOCA-91 Signature: A	Zone: CBL: 425-G-041
Proposed Project Description:		i i i i i i i i i i i i i i i i i i i	FIVITIES DISTRICT (PA)	D.) nicrofich
Construct Deck (16 x 10)		App Der	proved with Conditions: nied	Shoreland 72/9 Wetland Flood Zone
Permit Taken By: Mary Gresik	Date Applied For:	Signature:	Date:	☐ Subdivision ☐ Site Plan maj ☐minor ☐mm ☐
 This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. Building permits do not include plumbing, septic or electrical work. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work. 				☐ Variance ☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
				Historic Preservation ☑ Not in District or Landmark ☑ Does Not Require Review ☐ Requires Review
				Action:
I hereby certify that I am the owner of record of the authorized by the owner to make this application if a permit for work described in the application is	as his authorized agent and I agree to sissued, I certify that the code official	conform to all applicable lass authorized representative	ws of this jurisdiction. In add shall have the authority to en	lition, Denied /
areas covered by such permit at any reasonable ho				1 1 1
areas covered by such permit at any reasonable host of the such permit at a such permi	anger ADDRESS:	26 June 1997 DATE:	PHONE:	

City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Permit No: 9 Phone: Owner: Location of Construction: houlanger, James 120 Presumpscot St BusinessName: Lessee/Buyer's Name: Phone: Owner Address: 04103 Ptld. ME 772-3019 ermit Issued: Phone: Address: Contractor Name: JUL - 3 1997 Omner COST OF WORK: PERMIT FEE: Proposed Use: Past Use: 1,000.00 25.00 CITY OF PORT 2- Lam Same INSPECTION: FIRE DEPT.

Approved Use Group: Type: ☐ Denied CBL: Zone: Signature: Signature: Zoning Approval: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Proposed Project Description: Approved Action: Special Zone or Reviews: Approved with Conditions: □ Shoreland Construct Deck (16 x 10) Denied □ Wetland ☐ Flood Zone □ Subdivision Date: Signature: ☐ Site Plan maj ☐minor ☐mm ☐ Date Applied For: Permit Taken By: Mary Gresik 26 June 1997 Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. □ Conditional Use 2. □ Interpretation Building permits are void if work is not started within six (6) months of the date of issuance. False informa-3. ☐ Approved tion may invalidate a building permit and stop all work.. ☐ Denied Historic Preservation ☑ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review Action: ☐ Appoved CERTIFICATION ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been □Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 26 June 1997 PHONE: ADDRESS: DATE: SIGNATURE OF APPLICANT James Boulanger PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE **CEO DISTRICT** White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

COMMENTS

· · · · ·		
2-14-97 Lange tiles wer	I which to place I led	
meda frilling & sile of	S-led rome	
C-20 92 / Lind for with 2 win	tube for been uncted. all	
	und of my on the mining of	
earle ballusters on in plan		
	Inspection Record Type Date	ρ
	J. I.	•
	Foundation:	
	Framing:	
	Plumbing:	
	Final:	
	Other:	

BUILDING PERMIT REPORT

DATE: 3 July 97 ADDRESS: 120 Presum pscol s	7
REASON FOR PERMIT: TO CONSTRUCT 10×16' deck	
BUILDING OWNER: James Boulanger	ω <u>(</u>
CONTRACTOR: OWN & -	
PERMIT APPLICANT: James Boulanger APPROVAL: 4/ 42 ×8×10 ×	DENI ED

CONDITION(S) OF APPROVAL

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)

3. Precaution must be taken to protect concrete from freezing.

- 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.
- 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
- Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
 - 9. Headroom in habitable space is a minimum of 7'6".
- X-10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread, 7" maximum rise.
 - 11. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
 - 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
 - Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 - 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
 - 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
 - All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-2 and

I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)


- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
- 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 23. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 24. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
- 25. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.

26. 27.	All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade.	,
28.		
29.		!

bief of Code Enforcement

Marge Schmuckal

\uparrow \uparrow \uparrow \uparrow \uparrow \uparrow \uparrow	Date: 7/2/97
Applicant: James Bowlinger Address: 120 ReSum pscot St	<i>'</i>
Address: 120 KeSum PScot 8T	C-B-L: 425-G-41
CHECK-LIST AGAINST ZONING	ORDINANCE
Date- Existing 1913 zunte	of per microtiene
Zone Location - 7-5	
Interior or corner lot -	la .
Proposed Use/Work - Construct 16 x10	deck
Sewage Disposal - Cofy	
Lot Street Frontage -	
Front Yard - Ol	
Rear Yard - Oll, Rear Yard - 20 reg Not on Side yard S	
Side Yard - 8 reg (Not on Side yard &	ide St) 51 8 mm
Projections -	
Width of Lot -	. (
Height -	
Lot Area - 8,079 # Lot Coverage/Impervious Surface - 40% (-eg)	$\left(\begin{array}{c} 1 \\ 2 \end{array} \right)$
Lot Coverage/Impervious Surface - 40% (-elg 5	3231,24
Area per Family -	
Off-street Parking -	
Loading Bays -	24×41 = 984
Site Plan -	5 X7 35
Shoreland Zoning/Stream Protection -	10
Flood Plains -	4412
	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	16 x 10



PROVIDENCE ST.

BASIC GUIDELINES FOR DECK PERMITS

Materials needed to apply for permit:

- 1) Plot Plan A Bird's eye view of your property showing where all your buildings are located in relationship to the lot lines and each other. You need to show those distances (the front, rear and sides) in feet.
 - 2) <u>Construction Plan</u> Cross Section. What dimensional lumber/materials are being used and what is their make-up?
 - 3) Fee Based on cost of work labor/materials. 25.00 1st 1,000 worth of work, 5.00 each additional 1,000.

The following check-off sheet can be used in most circumstances:

Foundation		Frost wall, min 4' below grade
· /		Sone tubes, min 4' below grade, 6" min on footing, hard pan or bedrock
	-	Other
sill		Distance between foundation supports
Joist Size		2x6 2x8
Joist Span		
Distance Between Joists	X	16"oc 24"oc other
Decking	X	5/4 other/explain
Stair Construction		10" min tread 7 3/4" max riser
Guard Height	<u>V</u>	36" 42"
Guards shall be located along open-sided walking surfaces located 15 1/2" above the floor or below grade. Single family - min 36", all others 42", neasured vertically above the leading edge of the tread or adjacent walking surface. BOCA 1005.5/1021.2		
<u>Balusters</u>	<u>/</u> /۱	under 4"

Open guards shall have balusters or be of a solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.