


**PORTLAND CITY
ARCHITECTURE**
 55 NEWBURY STREET
 PORTLAND, ME 04101
 207.751.9000
 fax 207.751.2070
 info@portcityarch.com



CONSULTANTS

**Zukowski & Espino
Residence**
 52 Berwick
 Portland, Maine

NO.	DATE	DESCRIPTION
1	**	Design Review
* DATE OF SUBMISSION		

Date Issued: December 14, 2005
 Project Number: 050205
 Drawing Title:

ELECTRICAL

Drawn By: LAG
 Checked By: LAG
T2

ELECTRICAL KEY

	TV CONNECTION
	POWER OUTLET
	220 POWER OUTLET
	DATA OUTLET
	TELEPHONE OUTLET
	THERMOSTAT
	SMOKE DETECTOR
	EXHAUST FAN
	SURFACE CEILING LIGHT - J BOX
	IRIS DIRECTIONAL CEILING LIGHT (RECESSED)
	WALL MOUNTED LIGHT
	SINGLE SWITCH
	3 WAY SWITCH
	DIMMER SWITCH
	CABLE MTD FIXTURE
	RECESSED DOWNLIGHT
	IRIS RECESSED DOWNLIGHT
	IRIS - A LAMP WALL WASH
	IRIS - CORNER WALL WASH
	IRIS - LENSED SHOWER LIGHT
	IRIS - SLOTTED ACCENT
	IRIS - PINHOLE
	BASIC WALL WASHER - RECESSED
	BASIC RECESSED SHOWER LIGHT

ELECTRICAL PLAN - GENERAL NOTES

- A. VERIFY EXACT LOCATIONS AND EXACT FIXTURES WITH OWNER
- B. THE ENTIRETY OF ELECTRICAL OUTLETS IS NOT SHOWN. LOCATIONS OF OUTLETS ARE TO BE DETERMINED BY CODE. ANY OUTLETS SHOWN ON THESE DRAWINGS ARE ADDITIONAL OUTLETS DESIRED BY THE OWNER. FIELD VERIFY LOCATIONS OF ALL OUTLETS WITH OWNER.
- C. ALSO SEE ELEVATIONS FOR EXTERIOR LIGHTING.
- D. ALL EXTERIOR OUTLETS TO BE PROTECTED AS REQ'D.

TABLE 3606.2.6

MAXIMUM SPANS FOR HEADERS LOCATED OVER OPENINGS IN WALLS

SIZE OF HEADER ¹	HEADERS IN BEARING WALLS ²			HEADERS IN WALLS NOT SUPPORTING FLOORS OR ROOFS
	SIZE OF HEADER	SIZE OF HEADER	SIZE OF HEADER	
2 - 2 X 4	4	-	-	-
2 - 2 X 6	6	4	-	-
2 - 2 X 8	8	6	-	10
2 - 2 X 10	10	8	6	12
2 - 2 X 12	12	10	8	14

For S1: 1 inch = 25.4 mm, 1 foot 304.8 mm
 1. Nominal four-inch thick single headers may be substituted for double members.
 2. Spans are based on No. 2 Grade Lumber with ten-foot tributary floor and roof loads.