

NEW: Greenstar FS Series

Floor standing Combi or Heat-only boiler specifically designed for the replacement boiler market.





Combi Model Shown















Quick Reference Specifications

Floor Standing Models Model Name Part Number USA List Price Performance Specifications	Heating & Tankless Hot Water			Heating*				
	Combi 100 KWR28-3 7733600/982 \$4,811	combi.131 KWB35-3 77336 (1083 \$5,393	Combi 151 KWR42-3 7733600084 \$6,218	57 KB 16-3 7/3360007/ \$3,705	79 KBR21-3 7733600078 \$4,258	100 KBR28-3 7733600079 \$4,811	7733600080	151 KB 42-3 77336 0081 \$5769
Fuel	NG / LP (LP conversion kit included)			NG / LP (LP conversion kit included)				
Input Maximum (MBH)	100.8	131.9	151.6	57.2	79.2	100.8	131.9	151.6
Input Minimum (MBH)	34.6	36.0	36.0	12.9	23.9	24.6	36.0	36.0
AFUE	95%	95%	95%	95%	95%	95%	95%	95%
DHW Flow Max (ΔT at 72°F), GPM	2.65	3.2	4.0	not applicable				
Boiler Weight & Dims (W XHxD)	136 lbs	- 19 ⁹ / ₁₆ " x 41"	' x 21 ⁷ /ε"	132 lbs - 19 ⁹ / ₁₆ " x 41" x 21 ⁷ / ₈ "				

Gas Connection Size - 34"

Supply / Return Tappings - 11/4"

Venting Options

Domestic Water Supply

- ▶ 2" (50mm) or 3"(80 mm)
 - · Twin pipe PVC / CPVC
 - · M&G Duravent PolyPro & Centrotherm InnoFlue
 - ► Twin pipe PP
 - ► PP Flexible
- ► Concentric PP venting in a 3"/5" (80/125 mm) is available from Bosch

Bosch Thermotechnology Corp. Londonderry, NH • Ft. Lauderdale, FL General Inquiries: 1-866-642-3198 Contractor Technical Support: 1-800-283-3787

www.boschheatingandcooling.com

Optional Control



The FW200 digital thermostat and outdoor reset boiler control is an optional accessory which enables the boiler to be operated more efficiently by allowing the user to optimize the heating system.

Vent connection 3" PVC

not applicable

USA List Price \$328



 $[^]st$ Heat only Greenstar models may be used with indirect water tanks to provide domestic hot water.

One more puzzle solved.



New: Greenstar FS Series.

Replacing a boiler with a high efficiency boiler? Wall boilers are not the only option!


The 95% AFUE Greenstar FS series is designed to upgrade cast iron floor boilers to a ultra-high efficient condensing boiler at lower installed cost by simplifying the installation.

Greenstar FS Series:

- ► Footprint: Fits in the same footprint as an existing floor boiler, no added cost to build a wall or move the boiler to an outside wall
- ► Piping: Low loss header pre-piped "under-the-hood", no need for primary/secondary piping, pipes just like the existing boiler
- ► Wiring: Connection boxes (both high & low voltage) conveniently located on the back of the boiler for quick and easy connection
- ► Venting: Options include polypropylene (PP), flexible PP chimney liner, concentric PP kit, PVC or CPVC
- Controlling: Simplified control, no programming required (FW200 control sold separately)

All Greenstar Models

- ► Broad BTU Range: Floor and the Wall models with 95% AFUE and up to 5:1 modulation are available in 5 Heat-Only and 3 Combi sizes
- ▶ Simplified Installation: Integral pump is standard on all models
- ► Coated Heat Exchanger: Prevents scale build-up, reduces service, maintains high efficiency and extends the life of the boiler
- ► High DHW Output: Up to 4 GPM DHW output on combi models based on ΔT at 72°F. Large flat-plate heat exchanger allows for lower operating temperatures and larger ΔT in DHW mode for higher efficiency and condensing operation
- ► Proven Reliability: Over 2 million Greenstar boilers sold worldwide





Bosch Greenstar — the world's best selling condensing gas boiler — North America's best value