



FIRST FLOOR FRAMING PLAN

- FIRST FLOOR FRAMING NOTES:
1. See Structural Notes, Sheet S-1.
 2. Built-up girders, headers and beams shall be spiked w/ 3 rows of 16d nails @ 12" o.c.
 3. Provide metal hangers at all flush joist connections.
 4. Provide double joists below all upper parallel walls.
 5. Provide solid blocking at mid-span of floor joists.
 6. See architectural drawings for wall layout and dimensions.
 7. Provide (3) 2 x 10 headers over all openings unless noted.

SECOND FLOOR FRAMING PLAN

- SECOND FLOOR FRAMING NOTES:
1. See Structural Notes, Sheet S-1.
 2. Built-up girders, headers and beams shall be spiked w/ 3 rows of 16d nails @ 12" o.c.
 3. Provide metal hangers at all flush joist connections.
 4. Provide double joists below all upper parallel walls.
 5. Provide solid blocking at mid-span of floor joists.
 6. See architectural drawings for wall layout and dimensions.
 7. Provide (3) 2 x 10 headers over all openings unless noted.

ROOF FRAMING PLAN

- ROOF FRAMING NOTES:
1. See Structural Notes, Sheet S-1.
 2. Built-up girders, headers and beams shall be spiked w/ 3 rows of 16d nails @ 12" o.c.
 3. Provide metal hangers at all flush rafter connections.
 4. Provide (3) 2 x 10 window headers unless noted otherwise.
 5. See architectural drawings for wall layout and dimensions.
 6. See architectural drawings for wall layout and dimensions. Connections shall be per Simpson H.L.S. Seams & Hurricane Ties per Manufacturer's Instructions.

