



FIRST FLOOR FRAMING PLAN PLAN
 1/4" = 1'-0"

- NOTES:
- 1) SEE GENERAL NOTES ON DRAWING S-001.
 - 2) SEE FOUNDATION DWG S101 FOR INFORMATION REGARDING NEW ADDITION FOUNDATION AND DETAILS.
 - 3) (E) INDICATES EXISTING & (VIF) INDICATES VERIFY IN FIELD.
 - 4) * INDICATES ALIGN POST/COLUMN W/ POST ABOVE AND PROVIDE 2X BLOCKING ABOVE AND BELOW POST AT BEAD-TYP.
 - 5) INSTALL SOLID 2X VERTICAL BLOCKING WITHIN FLOOR SYSTEM ON TOP OF SILL BEHIND POST ABOVE (TYP).
 - 6) CONCRETE FOOTING SCHEDULE AS FOLLOWS:
 F1 - 2'-0" SQ X 10" THICK W/ 3-#4 EA WAY 3" CUL FROM BOTTOM.
 F2 - 1'-4" SQ X 8" THICK.
 F3 - 2'-6" SQ X 12" THICK W/ 4-#4 EA WAY 3" CUL FROM BOTTOM.

PROJECT NORTH

REV.	DESCRIPTION	DATE
1		1/1
0	FOR CONSTRUCTION	6/1/12

ISSUED FOR
 J.J.

CURRENT ISSUE STATUS:

STATE OF MAINE
 JOSEPH H. LEASURE
 No. 6242
 LICENSED PROFESSIONAL ENGINEER

NADEAU STOVER RESIDENCE
 ADDITIONS AND RENOVATIONS
 PORTLAND, MAINE

FIRST FLOOR FRAMING PLAN

SHEET TITLE:

DATE:

SCALE: AS NOTED

PROJECT NO. SHEET No.

DRAWN BY:

A/E OF RECORD:

S 102