City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: Permit No: James Wass 30 Woodlawn Ave. BusinessName: Lessee/Buyer's Name: Phone: Owner Address: SAA Permit Issued: S Phone: Contractor Name: Address: 221 Virginia St. Ptld, ME 04103 797-9531 ##DAvid DiRietro COST OF WORK: PERMIT FEE: Proposed Use: Past Use: SEP 2 7 1999 \$ 8,000 \$ 72.00 **FIRE DEPT.** □ Approved INSPECTION: 1 Family Same Use Group 3 Type: 5 ☐ Denied CBL: BOC 96 Signature: Signature: Zoning Approval: PEDESTRIAN ACTIVITIES DISTRICT (PAID.) Proposed Project Description: OLWIL Action: Approved Remove lower part of porch and rebuild and close in. Special Zone or Reviews: Approved with Conditions: Denied □ Wetland ☐ Flood Zone ☐ Subdivision Date: Signature: ☐ Site Plan mai ☐minor ☐mm ☐ Date Applied For: Permit Taken By: 9-17-99 UB Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. 2. □ Conditional Use □ Interpretation Building permits are void if work is not started within six (6) months of the date of issuance. False informa-3. ☐ Approved tion may invalidate a building permit and stop all work... ****Send To: David DiPietro □ Denied 221 Virginia ST. Portland, ME 04103 Historic Preservation Not in District or Landmark Does Not Require Review ☐ Requires Review PERMIT ISSUED WITH REQUIREMENTS Action: □Appoved CERTIFICATION ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 9-17-99 PHONE: ADDRESS: DATE: SIGNATURE OF APPLICANT PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE CEO DISTRICT

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

/	BUILDING PERMIT REP	
1	20 Marchaun	1 AVE. CBL: 435-A-645
DATE: \angle	E: 19SepTigg ADDRESS: 30 Wood/awn	
	SONFORPERMIT: <u>EXTERIOR</u> renovaTions	s on porch
REASON	SON FOR PERMIT: ZATE TO	
BUILDIN	LDING OWNER: Vames NGS	tractor David DiPieTro
	MIT APPLICANT:	TA COLOR
USE GR	GROUP $\frac{73-3}{}$ CONSTRUCTIO	JN TYPE
The City	City's Adopted Building Code (The BOCA National Building Code/1996 wi City's Adopted Mechanical Code (The BOCA National Mechanical Code/19	ith City Amendments) 1993)
	CONDITION(S) OF APPROPRIES permit is being issued with the understanding that the following conditions 32 433 435 436 437 # 3 oroved with the following conditions:	ROVAL
:	I want that the following conditions	is are met: 4/ *2, *11, *13 *27 *29
This per	permit is being issued with the understanding that the following conditions	/ / / / /
A32	35 × 36 × 37 × 11	
Approve	roved with the following conditions.	
,	- 4 11 11 Ct-t	and Codorol rules and 193VS
1. 2.	This permit does not excuse the applicant from meeting applicable State and Before concrete for foundation is placed, approvals from the Development 1	Review Coordinator and inspection Services must be comment.
£2.	Before concrete for foundation is placed, approvals from the Development (A 24 hour notice is required prior to inspection)" ALL LOT LINES	S SHALL BE CLEARLY MARKED
	BEFORE CALLING." Foundation drain shall be placed around the perimeter of a foundation that	t consists of gravel or crushed stone containing not more than
3.	Foundation drain shall be placed around the perimeter of a foundation that 10 percent material that passes through a No. 4 sieve. The drain shall extend the property of the drain is not high	end a minimum of 12 inches beyond the outside edge of the
	10 percent material that passes through a No. 4 sieve. The drain shall extend footing. The thickness shall be such that the bottom of the drain is not high footing. The	gher than the bottom of the base under the floor, and that the
	footing. The thickness shall be such that the bottom of the drain is not high top of the drain is not less than 6 inches above the top of the footing. The top of the drain is not less than 6 inches above the top of the footing.	top of the drain shall be covered with an approved litter
	top of the drain is not less than 6 inches above the top of the footing. The membrane material. Where a drain tile or perforated pipe is used, the investment of the presented with a	vert of the pipe or tile shall not be higher than the floor
	membrane material. Where a drain tile or perforated pipe is used, the inverse elevation. The top of joints or top of perforations shall be protected with a elevation.	an approved filter membrane material. The pipe of the shall be
	elevation. The top of joints or top of perforations shall be protected with a placed on not less than 2" of gravel or crushed stone, and shall be covered placed on not less than 2" of gravel or crushed stone, and shall be covered to the four states of the place of the protection of the four states of the protection o	I with not less than 6" of the same material. Section 1813.5.2
•	placed on not less than 2" of gravel or crushed stone, and shall be covered Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundations anchors shall be a minimum of ½" in diameter, 7" into the foundations anchors shall be a minimum of ½" in diameter, 7" into the foundations are the control of 2305 17).	oundation wall, minimum of 12" from corners of foundation and
4.	Foundations anchors shall be a minimum of 72 in diameter, 7 miles and 12 february holts. (Section 2305 17)	The part of the second that the second
	a maximum 6' o.c. between bolts. (Section 2305.17) Waterproofing and dampproofing shall be done in accordance with Section 1908.	n 1813.0 of the building code.
5.	Waterproofing and dampproofing shall be done in freezing. Section 1908. Precaution must be taken to protect concrete from freezing. Section 1908.	3.0
6.	Precaution must be taken to protect concrete from freezing. Section 1908. It is strongly recommended that a registered land surveyor check all founds	dation forms before concrete is placed. This is done to verify
7.	that the proper setbacks are maintained.	
_	that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group and the property which are constant to	roup R-1, R-2, R-3 or I-1 shall be separated from adjacent
8.	Private garages located <u>beneath habitable rooms</u> in occupancies in Use Gro interior spaces by fire partitions and floor/ceiling assembly which are cons	istructed with not less than 1-hour fire resisting raining. It was
	interior spaces by fire partitions and floor/ceiling assembly which are cons garages attached side-by-side to rooms in the above occupancies shall be c	completely separated from the interior spaces and the article area
	by means of ½ inch gypsum board or the equivalent applied to the garage in the above occupancies shall be compared to the gypsum board or the equivalent applied to the garage in the poor of the POCA (1996)	means of 1/2 inch gypsum board or the equivalent applied to the
	garage side. (Chapter 4, Section 407.0 of the BOCA/1996)	The DOCA National
	garage side. (Chapter 4, Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 1	12 of the City's Mechanical Code. (The BOCA National
9.	Mechanical Code/1993). Chapter 12 & NFPA 211	10 G the 1014 O of the City's Building
10		dance with Chapter 12, Section 1214.0 of the City's Bunding
10.	Code	the of aleysted walking surfaces
V 11	Code. Guardrails & Handrails: A guardrail system is a system of building compo	onents located near the open sides of elevated waitings and onents located near the lower lovel. Minimum height all Use
\ 11.	Guardrails & Handrails: A guardrail system is a system of building composition for the purpose of minimizing the possibility of an accidental fall from the	e walking surface to the lower level. William merger and open
	for the purpose of minimizing the possibility of an accidental fall from the Groups 42", except Use Group R which is 36". In occupancies in Use Groups 42", except Use Group R which is 36".	roup A, B, H-4, 1-1, 1-2, W and R and public garages and I
	Groups 42", except Use Group R which is 36". In occupancies in Use Groups are guards shall have balusters or be of solid material parking structures, open guards shall have balusters or be of solid material parking structures.	al such that a sphere will a diameter of a minimum of 3e4" bu
	parking structures, open guards shall have balusters or be of solid materia any opening. Guards shall not have an ornamental pattern that would prove the less than 30" but not more	ovide a ladder effect. (Handrans shall be a minute of
	any opening. Guards shall not have an ornamental pattern that would pronot more than 38". Use Group R-3 shall not be less than 30", but not more than 38". (Section	re than 38".) Handrails shall be on both sides of
	not more than 38". Use Group R-3 shall not be less than 30", but not more with an outside diameter of at least 1 1/4" and not greater than 2". (Section	ons 1021 & 1022.0) - Handrans sharr 50 on 50 m
	· · · · · · · · · · · · · · · · · · ·	
12.	Headroom in habitable space is a minimum of 7'6". (Section 1204.0)	17.70 All other Use Group minimum 11"
₹13.	Stair construction in Use Group R-3 & R-418 a minimum of 10 Read :	and 7 74" maximum rise. Thi other ess essi-
⊄ 13.	tread 7" maximum rise. (Section 1014.0)	00 1 1 1 2 (61911) 101/1/1
1.4	tread, 7" maximum rise. (Section 1014.0) The minimum headroom in all parts of a stairway shall not be less than 80.	30 inches. (6%") 1014.4
14.	The minimum headroom in all parts of a stairway shall not be less than 80 Every sleeping room below the fourth story in buildings of Use Groups R	and 1-1 Shall have at least one operation window or separate
15.	Every sleeping room below the fourth story in buildings of Use Groups R approved for emergency egress or rescue. The units must be operable fro	om the inside without the use of special knowledge of parameters and inches (1118mm) above
	approved for emergency egress or rescue. The units must be operable fro tools. Where windows are provided as means of egress or rescue they shall have a	hall have a still neight not more than 44 mones (1110man) as
	tools. Where windows are provided as means of egress or rescue they sha the floor. All egress or rescue windows from sleeping rooms shall have a	a minimum net clear opening neight difficultion of 2.7 sq. ft
	the floor. All egress or rescue windows from sleeping rooms shall have a (610mm). The minimum net clear opening width dimension shall be 20 i	inches (508mm), and a minimum net clear opening of 50.
	(OTOMAI). THE IMMINISTRATION OF THE PROPERTY O	••

(Section 1018.6)

Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it 16. directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1) All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self 17. closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0) The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automat 18. extinguishment. (Table 302.1.1) All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of 19. the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In all bedrooms In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved 20. type. (Section 921.0) The Fire Alarm System shall maintained to NFPA #72 Standard. 21. The Sprinkler System shall maintained to NFPA #13 Standard. 22. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 23. of the City's Building Code. (The BOCA National Building Code/1996) Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open 24. any street or sidewalk from the time of November 15 of each year to April 15 of the following year". The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification 25. from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics). 26. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done. All requirements must be met before a final Certificate of Occupancy is issued. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996). Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical

Code/1993). (Chapter M-16) Please read and implement the attached Land Use Zoning report requirements. Not to war

Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code. Glass and glazing shall meet the requirements of Chapter 24 of the building code.

All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code

between

38.

<u>X</u>36.

₹ 37.

Building Inspector McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 7/24/99

^{**}On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

JAMES WASS EXISTIMG 30 WOODHAWNAU PORTHAND ME 04103 2X10 HEHDEN 266 416 286 E41571146 HOUSE Lag boltego 13/4 Ph4 主 2×5 FASTERS. 5UB GRADE GRAVIL EXISTING 3 IF NOT The Pier 8 SAUNA TOBE Shall be on footing with auchon

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

30 (NOON (QUID AND)

Total Square Footage of Proposed Structure	Square Footage of Lot	Square Footage of Lot						
Tax Assessor's Chart, Block & Lot Number Chart# 435 Block# A Lot# 045	Owner: SAMES WAS	Telephone#:						
Owner's Address: '30 WOODLAWN AUE	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee \$ 8,000 \$ \$70						
Proposed Project Description: (Please be as specific as possible) REMOUE LOWER PART OF PARCH AND REBUILD AND CLOSE IN								
Contractor's Name, Address & Telephone DAVID DIPIETRO ZZI UIRGINIA Rec'd By D97-9531 POATMAND NOTE 04103 UB Current Use: PORCH JAM Proposed Use: PORCH SAME								
Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. •All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. •All plumbing must be conducted in compliance with the State of Maine Plumbing Code. •All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventililation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application:								
1) ACopy of Yo 2) A Copy of y Minor or Major site plan review will be required for the checklist outlines the minimum standards for a site plan	our Deed or Purchase and Sale Agree your Construction Contract, if avail. 3) A Plot Plan/Site Plan he above proposed projects. The attach hin. 4) Building Plans	able CITY OF PORTLAND, WIL						
Unless exempted by State Law, construction documents must be designed by a registered design professional								

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules

Location/Addressof Construction (include Portion of Building):

- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the office applicable to this permit.

í	anoree die provisions of die code	complicable to uns perilit.			
	Signature of applicant:	In OD	(aco	Date: 0/_/	7-99



Inspection Services Michael J. Nugent Manager

Department of Urban Development Joseph E. Gray, Jr. Director

CITY OF PORTLAND



Building or Use Permit Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

As an applicant for a building permit, you are about to enter into a relationship with our Office. We welcome any questions, comments or suggestions that will make the process more efficient. Attached you will find an application and some samples of the submissions you will provide at application time. Please read <u>ALL</u> of the information and if you need any further assistance please call 874-8703 or 874-8693.

Minor or Major site plan review will be required for the most of the above proposed projects.



JAMES CUASS

BO WOODLAWN AVE
PORTLAND ME

FUH HMHY(00M 4 06

ZIM ONHYLUSS SSHM SZIMHS

NO SUPPORT WALLS

