



FIRST FLOOR FRAMING PLAN

1/16"=1'-0"

NOTES:

- INDICATES DIRECTION OF 5 1/2" NORMAL WEIGHT CONCRETE SLAB ON 3/16" GALVANIZED METAL DECK (2 1/2" CONCRETE FILL OVER 3" DECK, 3 SPAN MIN), U.N.O. PROVIDE 6x6-W1.4xW1.4 W.W.F. TOP OF SLAB EL 113'-3 1/2" @ H.P. CONC THICKNESS IS MINIMUM. PROVIDE SUFFICIENT CONC TO ACCOUNT FOR STRUCTURE DEFLECTION. SEE SPECS.
- INDICATES BRACING. SEE BRACING ELEVATIONS DWG S1.8.
- INDICATES MOMENT CONNECTION. SEE DETAILS.
- REINFORCE CONC SLABS AROUND ALL FLOOR PENETRATIONS PER TYPICAL DETAILS DWG S3.1, U.N.O. COORD ALL OPENING SIZES & LOCATIONS W/ARCH & OTHER DISCIPLINE DWGS.
- UNLESS NOTED OTHERWISE, BEAMS TO BE PLACED AT EQUAL SPACES BETWEEN COL LINES.
- FOR COLUMN SIZES, SEE COLUMN SCHEDULE, DWG S1.7.
- C="XX" INDICATES CAMBER.
- INDICATES COURTYARD AREA. SEE ARCH/CIVIL DRAWINGS FOR ADDITIONAL INFORMATION.

