City of Portland, Maine - Buil	Owner;			
222 Virginia St. 04102		•	Phone:	Permit No: 000751
Owner A ddress;	Lessee/Buyer's Name:	Phone:	Business Name:	pro conservation of the co
Same_	Ecoscop Buyor S Munic.	i none.	Businessivaine.	H PERMIT ISSUED
Contractor Name:	Address:	Pho	one:	Permit Issued:
**Ruel Ordway/David Kenyon	The B Charles Allen Conn. Elit	4.10	one,	
Past Use:	Proposed Use:	COST OF WO	PERMIT FEE:	
	•	\$ _{210,00}	1.8	
Single Family	多数数数	FIRE DEPT. [273 1375	CITY OF PORTLAND
	13 (\$1200)\$		Denied Use Group 4-3 Ty	A Commence of the commence of
			ose Group 1919	Zones CBL:
		Signature:	Boc A94	400-8-021
Proposed Project Description:			ACTIVITIES DISTRICT (PA	Zoning Approval:
English English English E. Comment		Action:	Approved	
Replace Front & Rear Steps			Approved with Conditions:	□ Special Zone or Reviews: □ □ Shoreland
			Denied	□ □ Shoreland □ □ □ Wetland
e e e e e e e e e e e e e e e e e e e	e, karanan karan saratum erekari kirani mengelejari kiranam kirang ayan di	ent marketin and analysis and a second me		□ Flood Zone
		Signature:	Date:	☐Subdivision
Permit Taken By:	Date Applied For:			☐ Site Plan maj ☐minor ☐mm ☐
Gayle	(3))	July 10,2000		
1. This permit application does not preclude	the Applicant(s) from mosting small-all	,		Zoning Appeal
		e State and Federal rule	S.	☐ Variance ☐ Miscellaneous
2. Building permits do not include plumbin	_			☐ Conditional Use
3. Building permits are void if work is not s	tarted within six (6) months of the date of	issuance. False informa	a-	□Interpretation
tion may invalidate a building permit and	d stop all work	work		
				□Denied
				Historic Preservation
				☐ Not in District or Landmark ☐ Does Not Require Review
				Requires Review
			ur ISSI	JED TES
			PERMIT	MEN Action:
	CERTIFICATION		TH REQUIRE	
I hereby certify that I am the owner of record of	CERTIFICATION	1 11	PERMIT ISSI WITH REQUIRE	□ Appoved
I hereby certify that I am the owner of record of	ion as his authorized agent and I agent to	d work is authorized by	the owner of record and that I have	e been I LIApproved with Conditions
authorized by the owner to make this applicate if a permit for work described in the application	non as his authorized agent and I agree (c	conform to all applicat	ble laws of this jurisdiction. In add	dition, Defiled
areas covered by such permit at any reasonab	le hour to enforce the provisions of the	s aumorized represent	ative shall have the authority to en	ter all Date:
seems to voted by such points at any reasonab.	ie nous to enforce the provisions of the c	ode(s) applicable to suc	en permit	
CICALITY IDE OF LEDY CO.	•	July 10,2		- AND THE REAL PROPERTY OF THE PERTY OF THE
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	DERMIT ISSUED
				TI REQUIREMENTS
RESPONSIBLE PERSON IN CHARGE OF W	OBK TITLE	' t _a	DITONE	PERMIT ISSUED WITH REQUIREMENTS
OTION DED I ENDON IN CHARGE OF W	OKK, HILE		PHONE:	CEO DISTRICT
White	-Permit Desk Green-Assessor's C	anary-D.P.W. Pink-P	ublic File Ivory Card-Inspecto	

Location of Construction:	Owner:		Phone:	Permit No: 000751
222 Virginia St. 04102 Owner Address:	Basel S. Rideo	116	707_3101	00013=
	Lessee/Buyer's Name:	Phone:	Business Name: 191	T DEPART ISSUED
Contractor Name:	Address:	In In		Permit Issued:
**Ruel Ordway/David Kenyon	l '		one:	remit issued:
Past Use:	Proposed Use:	COSTORWO	ORK? ⁹⁻⁸⁰⁶¹ PERMIT FEE:	JUL 1 1 2000
Single Family	Same	\$210,00 FIRE DEPT.	☐ Approved INSPECTION: ☐ Denied Use Group:	e:50 PORTLAND
			300994 N	Zone; CBL: 400-B-021
Proposed Project Description:		Signature:	Signature: Aff	4 10 1
		•	vactivities district (p)(4)	DI DE PIRS
Replace Front & Rear St	teps	Action:	Approved Approved with Conditions:	Special Zone or Reviews:
ti o tropo od događaje state o tropo od obradanje so objekt podajeje o og ozgodaje je jedna og objekt i so obj		Denied Signature: Date:		□ Wetland □ Flood Zone □ Subdivision
Permit Taken By:	Date Applied For:	101Bitterior	Dutc.	☐ Site Plan maj ☐mingr ☐mm !
Gayle	GD	July 10,2000		
This parmit application 4		•		Zoning Appeal
This permit application does not preclude	□Variance			
 Building permits do not include plumbin Building permits are void if work is not st tion may invalidate a building permit and 	tarted within six (6) months of the date of	f issuance. False inform	a-	☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
·				Historic Preservation ☑ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review
				Action:
	CERTIFICATION			□Appoved
I hereby certify that I am the owner of record of authorized by the owner to make this application of a permit for work described in the application.	ion as his authorized agent and I agree t	o conform to all applica	ble laws of this jurisdiction. In add	been
f a permit for work described in the application areas covered by such permit at any reasonable	le hour to enforce the provisions of the	at a authorized represent code(s) applicable to suc	ative shall have the authority to end	Date:
		7-3-10-0	JANA	
ON ATTUDE OF A DRY AS		: JULV 10.2	. 6.1 6.2 6.3	
SNATURE OF APPLICANT	ADDRESS:	July 10, 2 DATE:	PHONE:	DERWIT ISSUED TO
GNATURE OF APPLICANT ESPONSIBLE PERSON IN CHARGE OF W		DATE:	PHONE:	PERMIT ISSUED PERMIT ISSUED VITH REQUIREMENTS

BUILDING PERMIT REPORT

The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993) City's Adopted Emiding Code (The

CONDITION(S) OF APPROVAL

This permit is being issued with the understanding that the following conditions are met:

- This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

 Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained.

 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."
- less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain shall be protected pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, a shall be covered with not less than 6" of the same material. Section 1813.5.2

 Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6" O.C. between bolts. Section 2305.17 Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not of gravel or crushed stone, and Where a drain 넑
- Waterproofing and dampproofing shall be done in accordance with <u>Section 1813.0</u> of the building code
- Precaution must be taken to protect concrete from freezing. Section 1908.0
- ģΦ 73 60 72 proper setbacks are maintained. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the
- spaces by lire partitions and Hoor/celling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)

 All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code) (Chapter 12 & NEED & 211) Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/celling assembly which are constructed with not less than I-hour fire resisting rating. Private garages attained by fire partitions and floor/celling assembly which are constructed with not less than I-hour fire resisting rating. Private garages attained by fire partitions and floor/celling assembly which are constructed with not less than I-hour fire resisting rating.
- Code/1993). Chapter 12 & NFPA 211
- purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42°. In occupancies in Use Group A,B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4° cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34° but not more than 38°. Exception: Handrails that form part of a guard shall have a height not less than than 36° and not more than 42°. Handrail grip size shall have a circular cross section with an outside diameter of at least 1 14° and not greater than 2°. (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)

 Headroom in habitable space is a minimum of 76°. (Section 1204.0)

 Stair construction in Use Group R-3 & R-4 is a minimum of 10° tread and 7 ½° maximum rise. All other Use Group minimum 11° tread.

 T maximum rise. (Section 1014.0) Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

- approved for emergency egress or rescue. The units must be operable from the inside without the use or special knowledge of square work. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4) The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
 Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. The minimum
- 9 Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
- ğ The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic

- 19 All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be In the immediate vicinity of bedrooms ; ; ;

- In each story within a dwelling unit, including basements
 A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- The Fire Alarm System shall be installed and maintained to NFPA #72 Standard
- The Sprinkler System shall be installed and maintained to NFPA #13 Standard
- All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the
- City's Building Code. (The BOCA National Building Code/1999)
 Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

 The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a
- design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection
- attics). Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces &
- electrical (min. 72 hours notice) and plumbing inspections have been done.

 All requirements must be met before a final Certificate of Occupancy is issued.

 All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all
- 133
- 30.
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical (Chapter M-16)
- 3
- 33 Bridging shall comply with Section 2305.16. Please read and implement the attached Land Use Zoning report requirements.

 Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.
- Ų,
- Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)
 All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999)
 FINAL CHOON FEMALE COND FOR STAIR QUESTIVE CONDENS CODE/1999) Fil

McDougall, PFD rises, Building Inspector

PSH 1/2600

Marge Schmuckal, Zoning Administrator

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE ***THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE

*****CERTIFICATE OF OCCUPANCY FEE S50.00

LT.2000, OR EQUIVALENT. OF THE BUILDINGCODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD ***** All PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL,(AS PER SECTION114.0