	Owner:	4	Phone:	Permit No. 783
145% Washington Ave	Tring Figureins	ica sink i	· 中等 在 第7点上等等点的 2.73有的表表的	] 000103
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	The second secon
SAA Contractor Name:				Penhicipaned: ISSUED
Contractor Name:	Address:	Phone:		Leuminsariad: 1920 FD
Past Use:	Proposed Use:	COST OF WORK:	PERMIT FEE:	
t dot Date	Proposed Ose:	\$ 1.000	\$ 30.00	JUL 1 4 2000
single femily	e in the contract of the contr	FIRE DEPT.	nied Use Group: 9-3Type: 56	CITY CBL-
Proposed Project Description:		Signature:	Signature: 74	Zoning Approval:
- reposite trojett Besonption,			FIVITIES DISTRICT (P.A.D.)	, Manager Visit of American
replace existing	porch decking	Ap	proved Exproved with Conditions: Expression	Shoreland □ Wetland
		Signature:	Date:	☐ Flood Zone ☐ Subdivision
Permit Taken By:	Date Applied For:	18		☐ Site Plan maj ☐minor ☐mm l
	1	61y 12 2000 K		Zoning Appeal
2. Building permits do not include plur	not started within six (6) months of the date of			☐ Variance ☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
	CERTIFICATION	I work is authorized by the	PERMIT ISSUED WITH REQUIREMENTS	
if a permit for work described in the appli	lication as his authorized agent and I agree to cation is issued, I certify that the code official anable hour to enforce the provisions of the co	conform to all applicable la 's authorized representative ode(s) applicable to such per	ws of this jurisdiction. In addition shall have the authority to enter all	, □ Denied
authorized by the owner to make this applif a permit for work described in the appli	lication as his authorized agent and I agree to cation is issued, I certify that the code official	conform to all applicable la 's authorized representative	ws of this jurisdiction. In addition shall have the authority to enter all	□Denied

#### BUILDING PERMIT REPORT

DATE: 12 July 2000 ADDRESS: 1458 Mashington Ave. CBL: 344-I-0/0
REASON FOR PERMIT: Keplace Porch decks
BUILDING OWNER: 6/10/1/2/20 Chello .
PERMIT APPLICANT: /CONTRACTOR PACE
USE GROUP: 19-3 CONSTRUCTION TYPE: 5 9 CONSTRUCTION COST: 1,000.0-PERMIT FEES: 30,00
The City's Adopted Building Code (The BOCA National Building code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)

### CONDITION(S) OF APPROVAL

This permit is being issued with the understanding that the following conditions are met: 火ルスラン メラら サルー

- This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
- 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING." Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A
- less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2

  Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6" O.C. between bolts. Section 2305.17 thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10

- 7000
- **∞** Waterproofing and dampproofing shall be done in accordance with <u>Section 1813.0</u> of the building code.

  Precaution must be taken to protect concrete from freezing. <u>Section 1908.0</u>

  It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the artic area by means of ½ inch gysum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)

  All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical
- Code/1993). Chapter 12 & NFPA 211
- a height not less than than 36" and not more than 42". Handrail grip size shall have a circular cross section with an outside diameter of at least 1/4" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7) Headroom in habitable space is a minimum of 7'6". (Section 1204.0) purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A,B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 1/2" maximum rise. All other Use Group minimum 11" tread 7" maximum rise. (Section 1014.0)
- The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4) Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All
- 5 Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- 8 All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
- The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

7/17

- **19**. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

- In each story within a dwelling unit, including basements
   A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- The Fire Alarm System shall be installed and maintained to NFPA #72 Standard.
- The Sprinkler System shall be installed and maintained to NFPA #13 Standard.
- 24 All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)

  Section 25 – 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any
- street or sidewalk from the time of November 15 of each year to April 15 of the following year.

  The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection
- 26 Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces &
- 27. electrical (min. 72 hours notice) and plumbing inspections have been done.

  All requirements must be met before a final Certificate of Occupancy is issued. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical
- Please read and implement the attached Land Use Zoning report requirements. Not to was Seller the Tolks to boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code Bridging shall comply with Section 2305.16.

Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)
All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building,Code/1999).

Fasiles Shall be Lise of believee? Foolings, 721005, 121005, Collumn 1999.

ffises, Building Inspector McDougall, PFD

ge Schmuckal, Zoning Administrator

\*\*On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE \*\*\*THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE

\*\*\*\*\*CERTIFICATE OF OCCUPANCY FEE \$50.00

LT.2000, OR EQUIVALENT. OF THE BUILDINGCODE ) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD \*\*\*\* All PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL,(AS PER SECTION114.0

### THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

#### Additions/Alterations/Accessory Structures Building or Use Permit Pre-Application

To Detached Single Family Dwelling
In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on any property within the



# People's Regional Opportunity Program

## 510 Cumberland Avenue, Portland, Maine 04101

Memorandum

Date: 7/12/00

To: City of Portland Building Permit office

From: Carla Peterson

PROP Housing Program Wanager

Re: Permit for Ethel Blanchette
1458 Washington Ave

Portland, ME

scrious health and safety problem to the her and her husband. Both clients are elderly. Blanchette currently has a porch attached to her home that is falling apart and presenting a This is in regards to a permit application for the home of Ethel Blanchette. Mrs

repair the porch on Aging and a faith based youth organization will be providing the materials and labor to PROP, in combination with the Maine State Housing Authority, Southern Maine Agency

items addressed will be brought to code. pressure treated lumber. The stairs or roof over the structure will not be removed. All The project entails removal of the existing decking and posts and replacement with new

client and mediate this potentially hazardous situation. we are not granted a permit prior to their arrival we will be unable to assist this elderly The youth will be in Portland the week of July 22 - 29, 2000 to work on area homes.

have any questions regarding this matter. Please contact me at 874-1140 extension 239 or Paul Wingfield at extension 242 if you

Thank you for your assistance.



