Location of Construction:	Owner:		Street, 04101, Tel: (2	7 & Permit No:
16 Regan Lane 04103 Owner Address:	Weil & Florence		1	100
SAA	Lessee/Buyer's Name:	Phone:	BusinessName:	
Contractor Name: Affordable Windows & Siding	Address:	Phone	:	Permit Band! I ISSUED
Past Use:	Proposed Use:	COST OF WORK	K: PERMIT FEE: \$ 25.60	JUN 1 8 1999
1-Family	Same	FIRE DEPT.	Approved INSPECTION: Use Group: Signature:	Zone: CBL _{348-C-045}
Proposed Project Description:			CTIVITIES DISTRICT (P./	Zoning Approval
Amendment to Permit \$990603. Original 14x20, amend to build 18x18 garage.		<i>F</i>	Approved Approved with Conditions: Denied	Special Zone or Reviews:
			Date:	□ Flood Zone □ Subdivision All 1
Permit Taken By: SP	Date Applied For:	June 15, 1999	Date.	☐ Site Plan maj ☐minor ☐mm t
 Building permits do not include plumbing, set Building permits are void if work is not started tion may invalidate a building permit and sto 	d within six (6) months of the date oop all work			☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
	Call for	Pick Up: 782-20	PERMIT ISSUED WITH REQUIREMENTS	Historic Preservation □ Not in District or Landmark □ Does Not Require Review □ Requires Review Action:
	CERTIFICATION			□Appoved
I hereby certify that I am the owner of record of the authorized by the owner to make this application a	as his authorized agent and I agree t	o conform to all applicable	laws of this jurisdiction. In a	ddition, Denied
if a permit for work described in the application is areas covered by such permit at any reasonable ho				Date:
		Jume 15, 1999)	
				I
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Additions/Alterations/Accessory Structures Building or Use Permit Pre-Application

To Detached Single Family Dwelling
In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment. HVAC equipment (air handling) or other types of work that may require special review must be included. Certification That I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable sof this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that the Code Official's visions of the codes applicable to this/parmit.	The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the difference is expansion to the Structure, a complete plot plan (Site Plan) must include: The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the difference is properly lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well-assaultion pools, garages and any other accessory structures. Scale and required zoning district setbacks 4) Building Plans (Sample Attached) Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures) Window and door schedules	All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. All plumbing must be conducted in compliance with the State of Maine Plumbing Code. All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. The must include the following with you application: 1) A Copy of Your Deed or Purchase and Sale Agreement	Sylame, Address & Telephone Selection of the Selection of Selection o	Description: (Please be as specific as possible)	hart Block & Lot Number S Block# C Lot#045 PMY + Colones Henry S Block# C Lot#045 PMY + Colones Henry
	Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment. HVAC equipment (air handling) or other types of work that may require special review must be included. Certification I hereby certify that I am the Owner of record of the named property. or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this/permit.	icabl	lectrical installation. mended by Section 6-Art III. BOCA Mechanical Code. If the distance of the section of	By: llectrical installation. umended by Section 6-Art III. BOCA Mechanical Code. Int DEPT OF BUILDING AND III. BOCA Mechanical Code. Int OF BUILDING AND III. BOCA Mechanical Code. Int OF BUILDING AND III. BOCA Mechanical Code. Int OF BUILDING AND III. INT OF BUILDING AND III	S S S S S S S S S S S S S S S S S S S
Telephone#: Cost Of Work: Fee S S S S S S S S S S S S	Telephon S Name (If Applicable) S Name (If Applicable) Cost Of Work: Rec'd By: Rec'd By: 1996 B.O.C.A. Building Code as amended by Sectical ire. 1996 B.O.C.A. Building Code as amended by Sectical Electrical Code as amended by Sectical Information must comply with the 1993 BOCA Me Purchase and Sale Agreement	Sor's Charl Block & Lot Number Owner: Some Address: Cost Of Work: Cost Of Work: Solica Description: (Please be as specific as possible) Solica Description: Address & Telaphóne Solica Description: Address & Telaphóne Solica Description: Recid By:	hart Block & Lot Number Block	hart Block & Lot Number () Owner Owner Hard Telephon () Block# C Lot#O45 Phil 4 + Colored Herd Telephon	

٠						
		١	3	ľ	۱	
		(۱	
		l				
		ļ			i	
		ì	•		ί	
				2		
		(ί		Ì	
		,	٦	d	ľ	
	i	ì	1	ij	١	
		١	7		•	
		١		Š	1	
		ļ			1	
		,		,	5	
		ļ	,	Ç	ĺ	
		ļ	7	7	ļ	
)	1	Į	ĺ	
		۱				
		į		Ų	ŀ	
		۱	_	1		

	بس
from the apartment to the building extensor with no communications to other apartment units. (Section 1010-1)	,
egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)	<u>.</u>
 The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4 Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or extenior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of euress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All 	نسز اسر
13. Star construction in Use Group K-3 & K-4is a minimum of 10" tread and 7%" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)	þes
Wand not greater than 2". (Sections 1021 & 1022.0) - Handralls shall be on both sides of stairway. (Section 10 Headroom in habitable space is a minimum of 76". (Section 1204.0)	٠ 🛏
except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handralls shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrall grip size shall have a circular cross section with an outside diameter of at least 1	
10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code. 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42",	, ,
9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211	ın
gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)	
8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch	~
	ý
_	
4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from comers of foundation and a	
less man o inches above the top of the bount. The top of the than statute covered with an approved intermediate whether whether than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and that he covered with an tiless than 6" of the same material. Section 1813 5 7	
percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not ligher than the bottom of the base under the floor, and that the top of the drain is not ligher than the bottom of the base under the floor, and that the top of the drain is not ligher than the bottom of the base under the floor, and that the top of the drain is not ligher than the bottom of the base under the floor.	
(2. Before concrete for foundation is placed, approvale from the Leaveschment Review Coerammer and inspection Services must be obtained. (A. 24 hour notice is required prior to inspection) 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10.	جعر
This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.	Y =
Approved with the following conditions: * / * * * * * * * * * * * * * * * * *	
This paraitie haing served with the understanding that the following conditions are met:	_
TONDEROUS OF THE CONTROL OF THE CONT	
PERMIT APPLICANT: UTITO OF 1996 CONSTRUCTION TYPE 512,	
Henderson	
REASON FOR PERMIT: To Amend Permit & 996693	
DATE: 17 June 99 ADDRESS: 16 Reggn Ad. CBL: 348-C-645	
POPULATION SERVING	

150

19.

The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be