Location of Construction: 142 Regan La	Owner:	6 Debo	<b></b> 章	Phor	ne:	Permit No: 980266			
Owner Address:	Lessee/Buyer's Name:		Phone:	Busi	nessName:	PERMIT ISSUED			
Contractor Name: David Dardano	Address: 38 West Lynn Av.		land, HE		878-3922	Permit Issued: MAR 2 4 1998			
Past Use:	Proposed Use:	C( \$	OST OF W	ORK:	PERMIT FEE: \$ 70.00				
E. row E. States	Same			☐ Approve☐ Denied	Use Group Type: Signature:	Zone: CBL:			
Proposed Project Description:				N ACTIVI	TIES DISTRICT (P.A.D.)	Zoning Approval:			
Make Interior Renovations	/Basemaut	Ac	tion:	Approve Approve Denied	ed CC Ed with Conditions: E	Shoreland			
Permit Taken By:	In	Sig	nature:		Date:	☐ Subdivision ☐ Site Plan maj ☐minor ☐mm [			
Hary Greate	Date Applied For:	20 Mar	ch 1998			Zoning Appeal			
<ol> <li>Building permits do not include plumb.</li> <li>Building permits are void if work is not tion may invalidate a building permit a</li> </ol>	started within six (6) months of the date of	issuance.	False inforn	na-		☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied			
				WITH	PERMIT ISSUED I REQUIREMENTS	Historic Preservation  ☑ Not in District or Landmark  ☑ Does Not Require Review  ☑ Requires Review			
					"ENIS	Action:			
I hereby certify that I am the owner of record authorized by the owner to make this application.	ation as his authorized agent and I agree to	conform	o all applic	able laws of	f this jurisdiction. In addition	, □ Denied			
if a permit for work described in the applicat areas covered by such permit at any reasona	ion is issued, I certify that the code official ble hour to enforce the provisions of the co	l's authori: ode(s) app	zed representicable to su	ntative shall uch permit	have the authority to enter al	Date:			
	1000 1. 2.00	. 1	20 Mes	rch adas		:			
SIGNATURE OF APPLICANT David Be	Artot, ar He Arton urdano ADDRESS:	- /	DATE:		PHONE:				
RESPONSIBLE PERSON IN CHARGE OF V	WORK, TITLE				PHONE:				
					HONE.	CEO DISTRICT			

## BUILDING PERMIT REPORT

15.	14.		72.11.	127.6	ó	7.	.60		Ņ	<b>.</b>	ပုံး	h j	Api	This	ISD	ग्रद	CO	RE BU	ДĄ
The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.	exits directly from the apartment to the building exterior with no communications to other apartment units.  All vertical openings shall be enclosed with construction having a fire rating of at less one (1) hour including fire documents.	knowledge or separate tools. Where windows are provided as means of egress or rescue than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a sill height not more opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.	11" tread. 7" maximum rise.  The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8")  Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window.	(Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2".  Headroom in habitable space is a minimum of 76".  Stair construction in Use Group R-3 & R-4 is a minimum of 10" trend and 7 3/4" maximum size. All at 1.1.	Surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Grands shall not have an opening the property of the control	71	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993).	rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the artic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 1 Section 1070 and 1.500 areas and 1.500 areas side.)	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floody literature.	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to	obtained. (A 24 hour notice is required prior to inspection)  Precaution must be taken to protect concrete from Favoring.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.  Before concrete for foundation is placed approvals from the Development Review Coordinator and Indicated approvals from the In	Approved with the following conditions: 4 1 x8 7 x 10 x 10 x 10 x 2 x 2 x 2 x 2 x 2 x 2 x 2 x 2 x 2 x	SUNDITION(S) OF APPROVAL  s Permit is being issued with the understanding that the following conditions are met-	USE GROUP 19 3 BOCA 1996 CONSTRUCTION TYPE 5 19	PERMIT APPLICANT:	CONTRACTOR: David Dardano	REASON FOR PERMIT: TO MOKE INTELION YOMUGITIONS BUILDING OWNER: Debandh OF OF Flahenty	DATE: 23 MAK 95 ADDRESS: 142 Regan (n

All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the