17.	All posted and the Late of the
17.	All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours (6) in 110 and (1) hour, including fire doors with self
18.	closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
10.	The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automat extinguishment. (Table 302.1.1)
19.	All single and multiple station ample datasets 1 11 1 2
.,,	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (ROCA National Building Code Chapter 9).
	the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke
	In the immediate vicinity of bedrooms
	In all bedrooms
	In each story within a dwelling unit, including basements
	IN AUGITURE TO THE FEORIFE AC DELIMARY POWER POWER PROCESS. 1. 1. 1. 1. 1.
	In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.
20.	A portable fire extinguisher shall be located as per NIFPA #10. The contestion is required) Section 920.3.2.
	type. (Section 921.0)
21.	The Fire Alarm System shall maintained to NFPA #72 Standard
22.	LUC DELIER STORM shall maintained to MEDA #12 Cr., 1 3
23,	All exit signs, lights and means of coress lighting shall be done in account of the state of the
	of the City's Building Code. (The BOCA National Building Code/1996)
24.	Section 20-100 of the Municipal Code for the City of postored states for the City of postored
0.5	any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
25.	
20	Inspection Services.
26. 27.	Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
21.	All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until
28.	all electrical (min.72 hours notice) and plumbing inspections have been done.
29.	An inquirements must be met before a tinal Cartificate of Commandia to the state of
47.	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
30.	Ventilation of consequitible a fact at a second sec
,00.	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
31.	Picase read and implement the etech-17 111
32.	Please read and implement the attached Land Use Zoning report requirements. Boring, cutting and notching shall be done in according report requirements.
33.	Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code. All singage shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
34.	All signage, shall be done in accordance with Section 2102 0 city of the building code.
	All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code, 1996).
35.	
36.	
37.	
8.	
v.	
	61
/ N	
Salua	Hoorses, Building Inspector
1//2	L. McDougall, PFD
. / .	· · · · · · · · · · · · · · · · · · ·

Marge Schmuckal, Zoning Administrator

PSH 7/24/99

^{**}On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

Type Foundation: Framing: Plumbing: Final: Other:	
Date	