

## City of Portland.

## OFFICE OF INSPECTOR OF BUILDINGS

	10-14-12
To	the Inspector of Buildings of the City of Portland:
Two	The undersigned respectfully makes application for a permit to erect enlarge a building on  Atlen Ave
CF	ELLAR WALL—To be constructed of Concrete to be 16 inches wide on bottom and batter to 12 inches on top.
	NDERPINNING—To be Brick Height of underpinning from top of cellar wall to bottom of sill
	XTERIOR WALLS—To be constructed of O.O.d
If	wood construction, sills to be4.4**
	tenements, or other family uses state number of families accommodated and number on each floor.  If for manufacturing or mercantile purposes state character of business and amount of estimated weight to be carried by the floor.)  One
	Total number of families
	Mercantile business (state character and load per sq. ft.)
	SIRESTOPS—All bearing and center partitions will have firestops cut in tight on top of each partition capand between each set of floor timbers. Where ledger boards are used there shall be firestops cut in tight against bottom of ledger boards, of same size as wall studs. Also wherever the Inspector of Buildings may consider necessary.
	STAIRWAYS—No. in buildinglocation
(	ROOF—To be constructed of
,	Dormer Windows to be made of
	Estimated Cost of Building 3000 INSPECTION—The Inspector of Buildings is to be notified when building is ready for lathing and at least 24 hours before the high begun.  Address
	The Architect is
	All floor timbers to he 2 kg. and 2 k. The and
1.6	inon.centers
	(Applieant to sign here D.M. Makalak.
	Athliteum on non and the sale of the